

View Online at <https://aerobasegroup.com/nsn/2320-00-904-3502>

Cylinder Quantity:

Any acceptable

Battery Quantity:

Any acceptable

Wheel Quantity:

6

Drive Wheel Quantity:

6

Prime Mover Type:

Any acceptable

Engine Brake Horsepower:

Any acceptable

Engine Horsepower Rating Speed In Rpm:

Any acceptable

Battery Voltage Rating In Volts:

Any acceptable

Reverse Speed Quantity:

Any acceptable

Transmission Type:

Manual

Forward Speed Quantity:

10

Maximum Load Rating:

24000.0 pounds

Tilting Feature:

Included or not included

Seating Capacity:

Any acceptable

Features Provided:

Outrigger and towing pintle hook and trailer brake connection and underwater fording system

Boom Operation Method:

Power

Gypsy Head:

Not included

Trailer Brake Connection Type:

Air

Rated Load Capacity:

12.00 tons

Drive Axle Location:

Front and rear

Axle Drive Type:

Conventional

Axle Speed Quantity:

Any acceptable

Front Axle Engaging Mechanism Type:

Manual

Rear Wheel Mounting Type:

Dual

Wheelbase:

Any acceptable

Front Wheel Tread Width:

Any acceptable

Rear Wheel Tread Width:

Any acceptable

Transmission Adjunct Type:

Transfer

Transmission Adjunct Speed Quantity:

2

Winch Location:

Behind cab

Winch Type:

Double drum

Boom Type:

Double fixed

Boom Maximum Length:

Any acceptable

Boom Operational Direction:

Rotating

Minimum Swing Angle In Deg:

Any acceptable

Crane Operation Type:

Any acceptable

Load Lifting Capacity Rating:

Any acceptable

Load Lifting Method:

Power

Cab Type:

Any acceptable

Cab Roof Type:

Closed or open

Brake Actuation Method:

Air

Cab Door Quantity:

Any acceptable

Special Features:

Class 44.5, size 24t, model 6x6

Specification Or Standard:

2 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A37500

Mil-std (military Standard):

Mil-t-62491 spec.