## NSN 2320-01-058-5725

Dump Truck - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2320-01-058-5725 **Cylinder Quantity: Battery Quantity:** Wheel Quantity: **Drive Wheel Quantity: Prime Mover Type:** Diesel engine **Engine Brake Horsepower:** Any acceptable **Engine Horsepower Rating Speed In Rpm:** Any acceptable **Battery Voltage Rating In Volts:** 12.0 **Reverse Speed Quantity: Transmission Type:** Manual **Forward Speed Quantity:** 13 **Seating Capacity: Features Provided:** Power steering and power take-off and tailgate and cab protector **Drive Axle Location:** Front and rear **Axle Drive Type:** Conventional **Axle Speed Quantity: Rear Wheel Mounting Type:** Dual Wheelbase:

Any acceptable **Front Wheel Tread Width:** Any acceptable **Rear Wheel Tread Width:** Any acceptable **Multifuel Design Feature:** 

Included or not included

## **NSN 2320-01-058-5725** Dump Truck - Page 2 of 2



| Transmission Adjunct Type:     |
|--------------------------------|
| Any acceptable                 |
| Cab Type:                      |
| Conventional                   |
| Cab Roof Type:                 |
| Closed                         |
| Brake Actuation Method:        |
| Air                            |
| Tailgate Operation Method:     |
| Power                          |
| Cargo Area Length:             |
| Any acceptable                 |
| Cargo Area Width:              |
| 84.00 inches                   |
| Cargo Area Height:             |
| Any acceptable                 |
| Side Removability:             |
| Nonremovable                   |
| Vehicle Maximum Gross Weight:  |
| 50000.00 pounds                |
| Cab Door Quantity:             |
| 2                              |
| Specification Or Standard:     |
| V type and e class and 2 group |
| Shelf Life:                    |
| N/a                            |
| Unit Of Measure:               |
|                                |
| Demilitarization:              |
| No                             |
| Fiig:                          |
| A37500                         |