## NSN 2320-01-333-9513

Stake Truck - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2320-01-333-9513

Body Material:
Steel and wood
Cylinder Quantity:
6
Battery Quantity:
1
Wheel Quantity:
6
Drive Wheel Quantity:
4
Prime Mover Type:
Diesel engine
Engine Brake Horsepower:
Any acceptable
Battery Voltage Rating In Volts:
12.0
Reverse Speed Quantity:
1
Transmission Type:
Manual
Forward Speed Quantity:
8
0
Hinge Location:
-
Hinge Location:
Hinge Location: Any acceptable
Hinge Location: Any acceptable Stake Type: Lattice panel
Hinge Location: Any acceptable Stake Type:
Hinge Location: Any acceptable Stake Type: Lattice panel Seating Capacity:
Hinge Location: Any acceptable Stake Type: Lattice panel Seating Capacity: 2
Hinge Location: Any acceptable Stake Type: Lattice panel Seating Capacity: 2 Features Provided:
Hinge Location: Any acceptable Stake Type: Lattice panel Seating Capacity: 2 Features Provided: Rear bumper and tailgate
Hinge Location: Any acceptable Stake Type: Lattice panel Seating Capacity: 2 Features Provided: Rear bumper and tailgate Rated Load Capacity:
Hinge Location: Any acceptable Stake Type: Lattice panel Seating Capacity: 2 Features Provided: Rear bumper and tailgate Rated Load Capacity: 2.50 tons
Hinge Location: Any acceptable Stake Type: Lattice panel Seating Capacity: 2 Features Provided: Rear bumper and tailgate Rated Load Capacity: 2.50 tons Drive Axle Location:
Hinge Location: Any acceptable Stake Type: Lattice panel Seating Capacity: 2 Features Provided: Rear bumper and tailgate Rated Load Capacity: 2.50 tons Drive Axle Location: Front and rear
Hinge Location: Any acceptable Stake Type: Lattice panel Seating Capacity: 2 Features Provided: Rear bumper and tailgate Rated Load Capacity: 2.50 tons Drive Axle Location: Front and rear Axle Drive Type:
Hinge Location: Any acceptable Stake Type: Lattice panel Seating Capacity: 2 Features Provided: Rear bumper and tailgate Rated Load Capacity: 2.50 tons Drive Axle Location: Front and rear Axle Drive Type: Single reduction
Hinge Location: Any acceptable Stake Type: Lattice panel Seating Capacity: 2 Features Provided: Rear bumper and tailgate Rated Load Capacity: 2.50 tons Drive Axle Location: Front and rear Axle Drive Type: Single reduction Rear Wheel Mounting Type:
Hinge Location: Any acceptable Stake Type: Lattice panel Seating Capacity: 2 Features Provided: Rear bumper and tailgate Rated Load Capacity: 2.50 tons Drive Axle Location: Front and rear Axle Drive Type: Single reduction Rear Wheel Mounting Type: Dual
Hinge Location: Any acceptable Stake Type: Lattice panel Seating Capacity: 2 Features Provided: Rear bumper and tailgate Rated Load Capacity: 2.50 tons Drive Axle Location: Front and rear Axle Drive Type: Single reduction Rear Wheel Mounting Type: Dual Wheelbase:

## **NSN 2320-01-333-9513** Stake Truck - Page 2 of 2



Rear Wheel Tread Width:
Any acceptable
Multifuel Design Feature:
Not included
Transmission Adjunct Type:
Transfer
Transmission Adjunct Speed Quantity:
2
Cab Type:
Conventional
Cab Roof Type:
Closed
Brake Actuation Method:
Air
Tailgate Operation Method:
Any acceptable
Cargo Area Length:
168.00 inches
Cargo Area Width:
92.00 inches
Cargo Area Height:
42.00 inches
Vehicle Maximum Gross Weight:
19000.00 pounds
Cab Door Quantity:
2
Special Features:
Rustproofed, heavy duty cooling system, mudflaps
Specification Data:
81348-kkk-t-2110e government specification
Specification Or Standard:
lii type and b class
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: