## NSN 2420-00-866-4129

Industrial Wheeled Tractor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2420-00-866-4129

| Engine Model Number:                               |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
| Model no. 601                                      |  |  |  |  |  |  |
| Engine Manufacturer Name:                          |  |  |  |  |  |  |
| Ford motor co                                      |  |  |  |  |  |  |
| Transmission Type:                                 |  |  |  |  |  |  |
| Hydraulic torque converter                         |  |  |  |  |  |  |
| Engine Type:                                       |  |  |  |  |  |  |
| Gasoline   |  |  |  |  |  |  |
| Front Wheel Drive Feature:                         |  |  |  |  |  |  |
| Not included                                       |  |  |  |  |  |  |
| Hinged Frame Steering System:                      |  |  |  |  |  |  |
| Not included                                       |  |  |  |  |  |  |
| Front Wheel Quantity:                              |  |  |  |  |  |  |
| 2  |  |  |  |  |  |  |
| Front Wheel Arrangement Characteristic:            |  |  |  |  |  |  |
| Single   |  |  |  |  |  |  |
| Front Tire Type:                                   |  |  |  |  |  |  |
| Pneumatic  |  |  |  |  |  |  |
| Front Wheel Steerable Feature:                     |  |  |  |  |  |  |
| Included   |  |  |  |  |  |  |
| Rear Wheel Quantity:                               |  |  |  |  |  |  |
| 2  |  |  |  |  |  |  |
| Rear Wheel Arrangement Characteristic:             |  |  |  |  |  |  |
| Single   |  |  |  |  |  |  |
| Rear Tire Type:                                    |  |  |  |  |  |  |
| Pneumatic  |  |  |  |  |  |  |
| Rear Wheel Drive Feature:                          |  |  |  |  |  |  |
| Included   |  |  |  |  |  |  |
| Rear Wheel Steerable Feature:                      |  |  |  |  |  |  |
| Not included                                       |  |  |  |  |  |  |
| Center To Center Tread Width Between Front Wheels: |  |  |  |  |  |  |
| 64.000 inches                                      |  |  |  |  |  |  |
| Center To Center Tread Width Between Rear Wheels:  |  |  |  |  |  |  |
| 64.000 inches                                      |  |  |  |  |  |  |
| Hard Surface Operation Limitation:                 |  |  |  |  |  |  |
| Unlimited  |  |  |  |  |  |  |
| Attachment Nomenclature And Quantity:              |  |  |  |  |  |  |
| Cab winter type                                    |  |  |  |  |  |  |
| Drawbar Pull:                                      |  |  |  |  |  |  |
| Between 0.0 pounds and 2500.0 pounds               |  |  |  |  |  |  |
| Shelf Life:  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |

## NSN 2420-00-866-4129

Industrial Wheeled Tractor - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

--

Demilitarization:

No

Fiig:

T277-v