# NSN 2510-00-706-7973

Fifth Wheel Kingpin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2510-00-706-7973

Head	

Between 0.546 inches and 0.578 inches

#### Flange Thickness:

Between 0.625 inches and 0.641 inches

# **Mounting Hole Diameter:**

0.875 inches

#### **Mounting End Type:**

Flange

#### **Body Length:**

Between 1.250 inches and 1.375 inches

#### **Body Outside Diameter:**

Between 2.870 inches and 2.880 inches

#### **Mounting Flange Bolt Hole Quantity:**

6

#### **Metallic Hardness Rating:**

20.0 rockwell c and 27.0 rockwell c

#### **Head Outside Diameter:**

Between 2.297 inches and 2.827 inches

#### **Shoulder Outside Diameter:**

Between 2.968 inches and 3.000 inches

# Flange Outside Diameter:

Between 8.000 inches and 8.500 inches

#### **Shoulder Length:**

Between 0.359 inches and 0.391 inches

#### Pin Length:

Between 3.625 inches and 3.688 inches

# **Mounting Hole Spacing:**

Equally spaced on 5-3/4 in. Bolt circle

#### Flange Shape:

Round

# **Locking Recess Outside Diameter:**

Between 1.995 inches and 2.005 inches

# **Locking Recess Length:**

Between 1.422 inches and 1.454 inches

# **Special Features:**

45 degrees chamfer on upper edge of bolt holes

#### Material:

Steel

# Material:

Steel

# **Style Designator:**

Locking recess

# NSN 2510-00-706-7973

Fifth Wheel Kingpin - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

Т305-е