NSN 2510-00-752-1826

Vehicular Leaf Spring Shackle Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2510-00-752-1826 **Concentric Hole Depth:** 2.250 inches **Concentric Hole Diameter:** 0.328 inches Pin Diameter: Between 0.990 inches and 0.991 inches Pinlength: 4.281 inches **Material Hardness Rating:** Between 50.0 rockwell c and 62.0 rockwell c **First Locking Groove Width:** 0.367 inches First Locking Groove Depth: 0.129 inches **Second Locking Groove Width:** 0.367 inches **Second Locking Groove Depth:** 0.129 inches **First Grease Relief Groove Width:** 0.666 inches First Grease Relief Groove Length: 0.367 inches First Grease Relief Groove Depth: 0.129 inches **Distance From End To First Grease Relief Groove:** 1.942 inches **Features Provided:** Casehardened **Special Features:** 0.188 in. W by 0.125 in. Deep slot, centrally located, in thd end Material: Steel **Material Specification:** Qq-s-633, c1019 or c1022, cold finished federal specification single material response **Style Designator:** Pin type, counterbore Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 2510-00-752-1826

Vehicular Leaf Spring Shackle Pin - Page 2 of 2



Fiig:

A02900