NSN 2510-01-041-5042

Overall Length: 55.500 inches

Suspension Torsion Bar - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2510-01-041-5042

Outside Diameter:
Between 1.525 inches and 1.535 inches
First End Thread Class:
2b
First End Thread Direction:
Right-hand
First End Chamfer Length:
0.120 inches
Second End Chamfer Length:
0.120 inches
First End Pitch Diameter:
1.750 inches
First End Internal Thread Length:
0.750 inches
Second End Pitch Diameter:
1.750 inches
Cover:
Not provided
First End Thread Size:
1/2-20
··
First End Thread Series/type Designator:
First End Thread Series/type Designator:
First End Thread Series/type Designator: Unf
First End Thread Series/type Designator: Unf Construction:
First End Thread Series/type Designator: Unf Construction: Solid
First End Thread Series/type Designator: Unf Construction: Solid Twist Direction:
First End Thread Series/type Designator: Unf Construction: Solid Twist Direction: Counterclockwise
First End Thread Series/type Designator: Unf Construction: Solid Twist Direction: Counterclockwise First End Cross-sectional Shape:
First End Thread Series/type Designator: Unf Construction: Solid Twist Direction: Counterclockwise First End Cross-sectional Shape: Serrated
First End Thread Series/type Designator: Unf Construction: Solid Twist Direction: Counterclockwise First End Cross-sectional Shape: Serrated First End Teeth Quantity:
First End Thread Series/type Designator: Unf Construction: Solid Twist Direction: Counterclockwise First End Cross-sectional Shape: Serrated First End Teeth Quantity: 28
First End Thread Series/type Designator: Unf Construction: Solid Twist Direction: Counterclockwise First End Cross-sectional Shape: Serrated First End Teeth Quantity: 28 First End Serration Length:
First End Thread Series/type Designator: Unf Construction: Solid Twist Direction: Counterclockwise First End Cross-sectional Shape: Serrated First End Teeth Quantity: 28 First End Serration Length: 1.000 inches
First End Thread Series/type Designator: Unf Construction: Solid Twist Direction: Counterclockwise First End Cross-sectional Shape: Serrated First End Teeth Quantity: 28 First End Serration Length: 1.000 inches First End Major Diameter:
First End Thread Series/type Designator: Unf Construction: Solid Twist Direction: Counterclockwise First End Cross-sectional Shape: Serrated First End Teeth Quantity: 28 First End Serration Length: 1.000 inches First End Major Diameter: Between 1.806 inches and 1.812 inches
First End Thread Series/type Designator: Unf Construction: Solid Twist Direction: Counterclockwise First End Cross-sectional Shape: Serrated First End Teeth Quantity: 28 First End Serration Length: 1.000 inches First End Major Diameter: Between 1.806 inches and 1.812 inches First End Pressure Angle In Deg:
First End Thread Series/type Designator: Unf Construction: Solid Twist Direction: Counterclockwise First End Cross-sectional Shape: Serrated First End Teeth Quantity: 28 First End Serration Length: 1.000 inches First End Major Diameter: Between 1.806 inches and 1.812 inches First End Pressure Angle In Deg: 45.00
First End Thread Series/type Designator: Unf Construction: Solid Twist Direction: Counterclockwise First End Cross-sectional Shape: Serrated First End Teeth Quantity: 28 First End Serration Length: 1.000 inches First End Major Diameter: Between 1.806 inches and 1.812 inches First End Pressure Angle In Deg: 45.00 Second End Cross-sectional Shape:

NSN 2510-01-041-5042Suspension Torsion Bar - Page 2 of 2



Second End Serration Length:
1.000 inches
Second End Major Diameter:
Between 1.806 inches and 1.812 inches
Second End Pressure Angle In Deg:
45.00
Solid Bar End Characteristic At First End:
Threaded hole
Solid Bar End Characteristic At Second End:
Plain
Special Features:
Positioning angle in degrees 40.50
Material:
Steel
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

T307-r