NSN 2510-01-318-7391

Engine Support Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2510-01-318-7391

End Application:

2350-01-115-1579

General Description:

 $Steel \ alloy; \ 10.250 \ in. \ Lg; \ 1.115 \ min \ 1.120 \ maximum \ in. \ Od, \ 0.375 \ in. \ W \ head; \ 1.052 \ min \ 1.062 \ maximum \ in. \ Od \ shank; \ 1.6875 \ in. \ Thd \ lg; \ 1.052 \ min \ 1.062 \ maximum \ in. \ Od \ shank; \ 1.6875 \ in. \ Thd \ lg; \ 1.052 \ min \ 1.062 \ maximum \ in. \ Od \ shank; \ 1.6875 \ in. \ Thd \ lg; \ 1.052 \ min \ 1.062 \ maximum \ in. \ Od \ shank; \ 1.6875 \ in. \ Thd \ lg; \ 1.052 \ min \ 1.062 \ maximum \ in. \ Od \ shank; \ 1.6875 \ in. \ Thd \ lg; \ 1.052 \ min \ 1.062 \ maximum \ in. \ Od \ shank; \ 1.6875 \ in. \ Thd \ lg; \ 1.052 \ min \ 1.062 \ maximum \ in. \ Od \ shank; \ 1.6875 \ in. \ Thd \ lg; \ 1.052 \ min \ 1.062 \ maximum \ in. \ Od \ shank; \ 1.6875 \ in. \ Thd \ lg; \ 1.052 \ min \ 1.062 \ maximum \ in. \ Od \ shank; \ 1.6875 \ in. \ Thd \ lg; \ 1.052 \ min \ 1.062 \ maximum \ in. \ Od \ shank; \ 1.6875 \ in. \ Thd \ lg; \ 1.052 \ min \ 1.062 \ maximum \ in. \ Od \ shank; \ 1.062 \ maximum \ in. \ Od \ s$

1.000 in. 14 nf-2a-lh

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli