## NSN 2520-00-150-7404

Vehicular Clutch Disk - Page 1 of 2

**Unable To Decode:** 



View Online at https://aerobasegroup.com/nsn/2520-00-150-7404

Unable to decode and unable to decode
Outside Diameter:
8.500 inches
Overall Length:
0.880 inches
Thickness:
Between 0.040 inches and 0.043 inches
Material Thickness:
Between 0.127 inches and 0.131 inches
Spline Quantity:
13
Bolt Hole Quantity:
6
Pitch Diameter:
0.8125 inches
Bolt Hole Diameter:
Between 0.194 inches and 0.198 inches
Design Type:
Dry
Material Location:
Both sides
Design Form:
Solid
Spline Pressure Angle In Deg:
30.0
Spline Type:
Involute
Bolt Hole Spacing:
Equally spaced on 3.781 in. Diameter bolt circle
Disk Type:
Plain
Material Outside Diameter:
Between 8.470 inches and 8.530 inches
Material Inside Diameter:
Between 5.340 inches and 5.410 inches
Facing Attachment Method:
Riveted
Damper Spring Quantity:
6
Distance From Flywheel Face To Rear Of Hub:
0.086 inches

## NSN 2520-00-150-7404

Vehicular Clutch Disk - Page 2 of 2



Features Provided:
Friction material facing and material facing groove
Construction:
Solid
Disk Material:
Steel
Special Features:
Damper spring encasement provision included; integral hub included; bolt hole included
Flexibility:
Flexible
Fsc Application Data:
Clutch, friction, vehicular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A521p0