NSN 2520-00-194-9917

Automotive Axle Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2520-00-194-9917

38.250 inches First End Spline Length: 3.500 inches First End Spline Minor Diameter: Between 1.925 inches and 1.927 inches First End Spline Major Diameter: Between 2.235 inches and 2.240 inches Second End Spline Length: 2.000 inches Second End Pitch Diameter: Between 2.381 inches and 2.385 inches First End Type: Splined Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Width: 0.125 in. From shaft end Second End Spline Type: Straight Material: Steel, sae 4340 Material: Steel comp 4340	Overall Length:
3.500 inches First End Spline Minor Diameter: Between 1.925 inches and 1.927 inches First End Spline Major Diameter: Between 2.235 inches and 2.240 inches Second End Spline Length: 2.000 inches Second End Pitch Diameter: Between 2.381 inches and 2.385 inches First End Type: Splined Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Facility Width: 0.875 inches Second End Facility Width: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	
3.500 inches First End Spline Minor Diameter: Between 1.925 inches and 1.927 inches First End Spline Major Diameter: Between 2.235 inches and 2.240 inches Second End Spline Length: 2.000 inches Second End Pitch Diameter: Between 2.381 inches and 2.385 inches First End Type: Splined Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Facility Width: 0.875 inches Second End Facility Width: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	First End Spline Length:
Between 1.925 inches and 1.927 inches First End Spline Major Diameter: Between 2.235 inches and 2.240 inches Second End Spline Length: 2.000 inches Second End Pitch Diameter: Between 2.381 inches and 2.385 inches First End Type: Splined Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	
Between 1.925 inches and 1.927 inches First End Spline Major Diameter: Between 2.235 inches and 2.240 inches Second End Spline Length: 2.000 inches Second End Pitch Diameter: Between 2.381 inches and 2.385 inches First End Type: Splined Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	First End Spline Minor Diameter:
Between 2.235 inches and 2.240 inches Second End Spline Length: 2.000 inches Second End Pitch Diameter: Between 2.381 inches and 2.385 inches First End Type: Splined Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Facility Width: 0.875 inches Second End Facility Width: 0.875 inches Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	
Between 2.235 inches and 2.240 inches Second End Spline Length: 2.000 inches Second End Pitch Diameter: Between 2.381 inches and 2.385 inches First End Type: Splined Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Facility Width: 0.875 inches Second End Facility Width: 0.875 inches Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	First End Spline Major Diameter:
2.000 inches Second End Pitch Diameter: Between 2.381 inches and 2.385 inches First End Type: Splined Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	
2.000 inches Second End Pitch Diameter: Between 2.381 inches and 2.385 inches First End Type: Splined Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Second End Spline Length:
Between 2.381 inches and 2.385 inches First End Type: Splined Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	
First End Type: Splined Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Second End Pitch Diameter:
Splined Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Between 2.381 inches and 2.385 inches
Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	First End Type:
Second End Type: Splined First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Splined
First End Spline Quantity: 10 Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	·
Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	
Second End Spline Quantity: 16 Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	First End Spline Quantity:
Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	10
Second End Facility Diameter: 1.875 inches First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Second End Spline Quantity:
First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	16
First End Bearing Seat: Not included Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Second End Facility Diameter:
Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	1.875 inches
Second End Spline Type: Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	First End Bearing Seat:
Involute Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Not included
Second End Spline Pressure Angle In Deg: 29.0 Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Second End Spline Type:
Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Involute
Second End Engaging/locking/positioning Facility: Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Second End Spline Pressure Angle In Deg:
Guide end Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	29.0
Second End Facility Width: 0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Second End Engaging/locking/positioning Facility:
0.875 inches Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Guide end
Second End Facility Location: 0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Second End Facility Width:
0.125 in. From shaft end Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	0.875 inches
Second End Bearing Seat: Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	Second End Facility Location:
Not included First End Spline Type: Straight Material: Steel, sae 4340 Material:	0.125 in. From shaft end
First End Spline Type: Straight Material: Steel, sae 4340 Material:	Second End Bearing Seat:
Straight Material: Steel, sae 4340 Material:	Not included
Material: Steel, sae 4340 Material:	First End Spline Type:
Steel, sae 4340 Material:	Straight
Material:	Material:
	Steel, sae 4340
Steel comp 4340	Material:
	Steel comp 4340

NSN 2520-00-194-9917

Automotive Axle Shaft - Page 2 of 2



Material Specification	V	late	rial	Spe	cific	cation	۱:
------------------------	---	------	------	-----	-------	--------	----

Sae 4340 assn standard single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T306-d