

View Online at <https://aerobasegroup.com/nsn/2520-00-334-4191>

Spline Minor Diameter:

1.125 inches

Spline Major Diameter:

1.375 inches

Slot Width:

0.125 inches

Overall Length:

1.750 inches

Thickness:

Between 0.064 inches and 0.070 inches

Material Thickness:

Between 0.156 inches and 0.161 inches

Spline Quantity:

10

Largest Outside Diameter:

Between 12.860 inches and 12.875 inches

Design Type:

Dry

Material Location:

Both sides

Design Form:

Solid

Spline Type:

Straight

Disk Type:

External slot

Asbestos Composition Type:

Metal impregnated

Material Outside Diameter:

Between 12.844 inches and 12.875 inches

Material Inside Diameter:

Between 7.234 inches and 7.266 inches

Facing Attachment Method:

Riveted

Distance From Flywheel Face To Rear Of Hub:

0.906 inches

Smallest Inside Diameter:

Between 2.254 inches and 2.262 inches

Angle Between Slots In Deg:

60.000

Features Provided:

Friction material facing and material facing groove

Construction:

Solid

Disk Material:

Steel

Special Features:

Integral hub included

Flexibility:

Rigid

Material:

Asbestos

Fsc Application Data:

Clutch assembly, vehicular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A521p0