

View Online at <https://aerobasegroup.com/nsn/2520-00-352-5518>

Spline Minor Diameter:

Between 1.221 inches and 1.227 inches

Spline Major Diameter:

Between 1.506 inches and 1.512 inches

Slot Width:

0.125 inches

Overall Length:

2.000 inches

Thickness:

Between 0.071 inches and 0.098 inches

Material Thickness:

Between 0.137 inches and 0.145 inches

Spline Quantity:

10

Largest Outside Diameter:

13.875 inches

Design Type:

Dry

Material Location:

Both sides

Design Form:

Solid

Spline Type:

Straight

Disk Type:

External slot

Asbestos Composition Type:

Wire woven

Material Outside Diameter:

Between 13.688 inches and 13.750 inches

Material Inside Diameter:

Between 7.219 inches and 7.281 inches

Facing Attachment Method:

Riveted

Distance From Flywheel Face To Rear Of Hub:

2.719 inches

Smallest Inside Diameter:

Between 2.632 inches and 2.636 inches

Angle Between Slots In Deg:

60.000

Features Provided:

Friction material facing and material facing groove

Construction:

Solid

Disk Material:

Steel

Special Features:

Integral hub included

Flexibility:

Rigid

Material:

Asbestos

Fsc Application Data:

Automotive clutch assembly, truck chassis

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A521p0