

View Online at <https://aerobasegroup.com/nsn/2520-00-352-5518>

**Spline Minor Diameter:**

Between 1.221 inches and 1.227 inches

**Spline Major Diameter:**

Between 1.506 inches and 1.512 inches

**Slot Width:**

0.125 inches

**Overall Length:**

2.000 inches

**Thickness:**

Between 0.071 inches and 0.098 inches

**Material Thickness:**

Between 0.137 inches and 0.145 inches

**Spline Quantity:**

10

**Largest Outside Diameter:**

13.875 inches

**Design Type:**

Dry

**Material Location:**

Both sides

**Design Form:**

Solid

**Spline Type:**

Straight

**Disk Type:**

External slot

**Asbestos Composition Type:**

Wire woven

**Material Outside Diameter:**

Between 13.688 inches and 13.750 inches

**Material Inside Diameter:**

Between 7.219 inches and 7.281 inches

**Facing Attachment Method:**

Riveted

**Distance From Flywheel Face To Rear Of Hub:**

2.719 inches

**Smallest Inside Diameter:**

Between 2.632 inches and 2.636 inches

**Angle Between Slots In Deg:**

60.000

**Features Provided:**

Friction material facing and material facing groove

**Construction:**

Solid

**Disk Material:**

Steel

**Special Features:**

Integral hub included

**Flexibility:**

Rigid

**Material:**

Asbestos

**Fsc Application Data:**

Automotive clutch assembly, truck chassis

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A521p0