

View Online at <https://aerobasegroup.com/nsn/2520-00-379-4306>

Spline Minor Diameter:

Between 1.218 inches and 1.221 inches

Spline Major Diameter:

Between 1.503 inches and 1.506 inches

Outside Diameter:

12.875 inches

Overall Length:

2.000 inches

Thickness:

Between 0.078 inches and 0.082 inches

Material Thickness:

Between 0.140 inches and 0.145 inches

Spline Quantity:

10

Bolt Hole Quantity:

10

Bolt Hole Diameter:

Between 0.260 inches and 0.266 inches

Design Type:

Dry

Material Location:

Both sides

Design Form:

Split

Spline Type:

Straight

Bolt Hole Spacing:

2.880 in. Max, 0.260 in. Min c to c dim of rivet holes

Disk Type:

Plain

Asbestos Composition Type:

Wire woven

Material Outside Diameter:

12.875 inches

Material Inside Diameter:

7.250 inches

Facing Attachment Method:

Riveted

Distance From Flywheel Face To Rear Of Hub:

1.469 inches

Features Provided:

Friction material facing and material facing groove

Construction:

Solid

Disk Material:

Steel

Special Features:

Integral hub and bolt hole included

Flexibility:

Rigid

Material:

Asbestos

Fsc Application Data:

Vehicular power transmission components

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A521p0