

View Online at <https://aerobasegroup.com/nsn/2520-00-379-4306>

**Spline Minor Diameter:**

Between 1.218 inches and 1.221 inches

**Spline Major Diameter:**

Between 1.503 inches and 1.506 inches

**Outside Diameter:**

12.875 inches

**Overall Length:**

2.000 inches

**Thickness:**

Between 0.078 inches and 0.082 inches

**Material Thickness:**

Between 0.140 inches and 0.145 inches

**Spline Quantity:**

10

**Bolt Hole Quantity:**

10

**Bolt Hole Diameter:**

Between 0.260 inches and 0.266 inches

**Design Type:**

Dry

**Material Location:**

Both sides

**Design Form:**

Split

**Spline Type:**

Straight

**Bolt Hole Spacing:**

2.880 in. Max, 0.260 in. Min c to c dim of rivet holes

**Disk Type:**

Plain

**Asbestos Composition Type:**

Wire woven

**Material Outside Diameter:**

12.875 inches

**Material Inside Diameter:**

7.250 inches

**Facing Attachment Method:**

Riveted

**Distance From Flywheel Face To Rear Of Hub:**

1.469 inches

**Features Provided:**

Friction material facing and material facing groove

**Construction:**

Solid

**Disk Material:**

Steel

**Special Features:**

Integral hub and bolt hole included

**Flexibility:**

Rigid

**Material:**

Asbestos

**Fsc Application Data:**

Vehicular power transmission components

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A521p0