NSN 2520-00-559-0434

Vehicular Clutch Disk - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2520-00-559-0434

Outside Diameter:
12.000 inches
Overall Length:
1.469 inches
Thickness:
0.350 inches
Material Thickness:
0.140 inches
Spline Quantity:
10
Design Type:
Dry
Material Location:
Both sides
Design Form:
Solid
Spline Type:
Involute
Disk Type:
Plain
Asbestos Composition Type:
Woven
Woven Material Outside Diameter:
Material Outside Diameter:
Material Outside Diameter: 11.875 inches
Material Outside Diameter: 11.875 inches Material Inside Diameter:
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches Facing Attachment Method:
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches Facing Attachment Method: Riveted
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches Facing Attachment Method: Riveted Damper Spring Quantity:
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches Facing Attachment Method: Riveted Damper Spring Quantity: 6
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches Facing Attachment Method: Riveted Damper Spring Quantity: 6 Features Provided:
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches Facing Attachment Method: Riveted Damper Spring Quantity: 6 Features Provided: Friction material facing
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches Facing Attachment Method: Riveted Damper Spring Quantity: 6 Features Provided: Friction material facing Construction:
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches Facing Attachment Method: Riveted Damper Spring Quantity: 6 Features Provided: Friction material facing Construction: Solid
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches Facing Attachment Method: Riveted Damper Spring Quantity: 6 Features Provided: Friction material facing Construction: Solid Disk Material:
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches Facing Attachment Method: Riveted Damper Spring Quantity: 6 Features Provided: Friction material facing Construction: Solid Disk Material: Nickel alloy
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches Facing Attachment Method: Riveted Damper Spring Quantity: 6 Features Provided: Friction material facing Construction: Solid Disk Material: Nickel alloy Special Features:
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches Facing Attachment Method: Riveted Damper Spring Quantity: 6 Features Provided: Friction material facing Construction: Solid Disk Material: Nickel alloy Special Features: Integral hub included
Material Outside Diameter: 11.875 inches Material Inside Diameter: 6.750 inches Facing Attachment Method: Riveted Damper Spring Quantity: 6 Features Provided: Friction material facing Construction: Solid Disk Material: Nickel alloy Special Features: Integral hub included Flexibility:

NSN 2520-00-559-0434

Vehicular Clutch Disk - Page 2 of 2



-				
٠.	hΔ	Iŧ.	ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A521p0