## NSN 2520-00-564-4243

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2520-00-564-4243 **Body Material:** Aluminum alloy First End Outside Diameter: 0.500 inches **Mounting Provision:** Threaded mounting holes **Tempurature Rating:** Not rated **Overall Height:** 2.828 inches **Overall Width:** 2.531 inches **Bore Diameter:** 1.750 inches **Body Outside Diameter:** 2.125 inches **Longest Horizontal Distance Between Mounting Centers: 3.188** inches **Longest Vertical Distance Between Mounting Centers:** 1.625 inches **Mounting Facility Thread Class:** 2b **Mounting Facility Thread Direction:** Right-hand First End External Thread Length: 1.000 inches **Compressed Length:** 9.688 inches **Extended Length:** 10.750 inches **Mounting Provision Arrangement Style:** Four hole rectangular **Pressure Rating:** Not rated **Mounting Facility Thread Series Designator: Mounting Facility Thread Diameter:** Mounting Facility Thready Qty Per Inch (tpi):

0.312 inches **Integral Valve Operation Method:** 

Pneumatic

## NSN 2520-00-564-4243

Linear Actuating Cylinder Assembly - Page 2 of 2



Design Characteristics:
Double acting single cylinder
First Piston Rod End Style:
External threaded
First Piston Rod End Thread Series Designator:
Unf
First Piston Rod End Thread Diameter:
0.500 inches
First Piston Rod End Thready Qty Per Inch (tpi):
20
First Piston Rod End Thread Class:
2a
First Piston Rod End Thread Direction:
Right-hand
Mounting Type And Location:
Flange center section
Mounting Facility Thread Length:
0.594 inches
Port Location And Quantity:
2 center section
Port Style:
Gasket seal
Port Thread Series Designator:
Npt
Port Pipe Thread Size:
0.250 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:

A34200