NSN 2520-00-620-3814

Vehicular Clutch Disk - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2520-00-620-3814

| Outside Diameter: |
|--|
| Between 6.490 inches and 6.500 inches |
| Thickness: |
| Between 0.088 inches and 0.097 inches |
| Material Thickness: |
| Between 0.029 inches and 0.038 inches |
| Design Type: |
| Dry |
| Material Location: |
| Both sides |
| Tooth Arrangement: |
| Continuous |
| Design Form: |
| Solid |
| Disk Type: |
| Internal teeth |
| Material Outside Diameter: |
| Between 6.400 inches and 6.430 inches |
| Material Inside Diameter: |
| Between 3.479 inches and 3.489 inches |
| Facing Attachment Method: |
| Bonded |
| Teeth Quantity Per Disk: |
| 19 |
| Teeth Pitch Diameter: |
| 3.167 inches |
| Features Provided: |
| Friction material facing |
| Construction: |
| Solid |
| Disk Material: |
| Steel |
| Flexibility: |
| Rigid |
| Material: |
| Copper alloy |
| Fsc Application Data: |
| Transmission assembly, tractor mtd scoop type loader |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 2520-00-620-3814

Vehicular Clutch Disk - Page 2 of 2



Demilitarization:

No

Fiig:

A521p0