

View Online at <https://aerobasegroup.com/nsn/2520-00-657-8569>

Spline Minor Diameter:

Between 1.706 inches and 1.712 inches

Spline Major Diameter:

Between 2.002 inches and 2.008 inches

Slot Width:

0.219 inches

Overall Length:

2.313 inches

Thickness:

0.085 inches

Material Thickness:

0.187 inches

Spline Quantity:

6

Largest Outside Diameter:

16.750 inches

Design Type:

Dry

Material Location:

Both sides

Design Form:

Solid

Spline Type:

Straight

Disk Type:

External slot

Asbestos Composition Type:

Wire woven

Material Outside Diameter:

16.750 inches

Material Inside Diameter:

10.000 inches

Facing Attachment Method:

Riveted

Distance From Flywheel Face To Rear Of Hub:

1.188 inches

Smallest Inside Diameter:

10.125 inches

Angle Between Slots In Deg:

60.000

Features Provided:

Friction material facing

Construction:

Solid

Disk Material:

Steel

Special Features:

Oil deflector quantity: 2; oil deflector outside diameter: 9.688 in. ; integral hub included

Flexibility:

Rigid

Fsc Application Data:

Friction clutch, high speed tractor

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A521p0