NSN 2520-00-820-3131

Vehicular Clutch Disk - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2520-00-820-3131

| Outside Diameter: |
|---|
| 2.531 inches |
| Thickness: |
| Between 0.057 inches and 0.063 inches |
| Material Thickness: |
| 0.032 inches |
| Design Type: |
| Dry |
| Material Location: |
| Both sides |
| Tooth Arrangement: |
| Continuous |
| Design Form: |
| Solid |
| Disk Type: |
| External teeth |
| Asbestos Composition Type: |
| Molded |
| Material Outside Diameter: |
| 2.531 inches |
| Material Inside Diameter: |
| 0.906 inches |
| Facing Attachment Method: |
| Bonded |
| Teeth Quantity Per Disk: |
| 22 |
| Teeth Pitch Diameter: |
| 2.750 inches |
| Features Provided: |
| Friction material facing |
| Construction: |
| Solid |
| Disk Material: |
| Steel |
| Flexibility: |
| Rigid |
| Material: |
| Asbestos |
| Fsc Application Data: |
| Overload, traversing mechanism, vehicular |
| Shelf Life: |
| |

N/a

NSN 2520-00-820-3131

Vehicular Clutch Disk - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A521p0

