NSN 2520-00-902-1979

Intermediate Clutch Hub - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2520-00-902-1979

General Description:

No

Cast iron, sae 60003, 7.625 in. Od, 2.139 in. Id, 2.881 in. Lg o/a, externally and internally splined, 60 external splines, 30 degrees pressured iron, sae 60003, 7.625 in. Od, 2.139 in. Id, 2.881 in. Lg o/a, externally and internally splined, 60 external splines, 30 degrees pressured iron, sae 60003, 7.625 in. Od, 2.139 in. Id, 2.881 in. Lg o/a, externally and internally splined, 60 external splines, 30 degrees pressured iron, sae 60003, 7.625 in. Od, 2.139 in. Id, 2.881 in. Lg o/a, externally and internally splined, 60 external splines, 30 degrees pressured iron, sae 60003, 7.625 in. Od, 2.139 in. Id, 2.881 in. Lg o/a, externally and internally splined, 60 external splines, 30 degrees pressured iron, sae 60003, 7.625 in. Od, 2.139 in. Id, 2.881 in. Lg o/a, externally and internally splined, 60 external splines, 30 degrees pressured iron, sae 60003, 7.625 in. Od, 2.139 in. Id, 2.881 in. Lg o/a, externally splined, 60 external splines, 30 degrees pressured iron, sae 60003, 7.625 in. Od, 2.139 in. Id, 2.881 in.
angle, 8/16 pitch, 35 internal splines, 30 degrees pressure angle, 16/32 pitch

Cast iron, sae 60003, 7.625 in. Od, 2.139 in. Id, 2.881 in. Lg o/a, externally and internally splined, 60 external splines, 30 degrees pressure
angle, 8/16 pitch, 35 internal splines, 30 degrees pressure angle, 16/32 pitch
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: