NSN 2520-00-905-7533

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2520-00-905-7533 **Body Material:** Steel, corrosion resisting First End Outside Diameter: 0.313 inches **Tempurature Rating:** 125.0 degrees fahrenheit **Overall Height:** 1.500 inches **Overall Width:** 1.500 inches **Bore Diameter:** 1.125 inches First End External Thread Length: 0.500 inches **Compressed Length:** 5.438 inches **Extended Length: 7.438** inches **Pressure Rating:** 150.0 pounds per square inch **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 0.313 inches First Piston Rod End Thready Qty Per Inch (tpi): 24 **First Piston Rod End Thread Class: First Piston Rod End Thread Direction:** Right-hand **Port Location And Quantity:** 1 piston rod end Port Style: **Port Thread Series Designator:**

Gasket seal Nptf Port Pipe Thread Size: 0.125 inches

NSN 2520-00-905-7533

Linear Actuating Cylinder Assembly - Page 2 of 2



Special	Features:
---------	-----------

 $Two \ mounting \ holes \ for \ no.10 \ screws \ in \ piston \ rod \ end, \ 90 \ degrees \ from \ port \ side, \ 0.250 \ in. \ From \ cylinder \ head \ end, \ 1.125 \ in. \ C \ to \ column{2}{c}$

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A34200