NSN 2520-01-106-9175

Shroud - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2520-01-106-9175

Test Data Document:

19207-11649049 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

General Description:

Steel low carbon hrcq or cpcq perqq-s-698; side view; 1.620 in.H; there are 2 raduis covers 0.190r 2pl; 1st raduis turning to right 0.190r; 1.750 in.W; 2nd raduis corner turning up 0.190r; 2.750 in.H; cover front view; cover 4.750 in.Lg; 2 identical slots; 1 on the left and 1 on the right; depth of 0.810 in.2 pl; 2 identical raduis corves on the end of the slot 2 pl; centerto center of 3.500 in.Lg; slot 0.340 in.2 pl.W; from the center slot to the outside wall 0.620 in.W; 2 identical 0.380 x 45 cham 2 places; from center of slot to inside slot wall 0.170 in.2 pl; top view; 1 panel divided in 2 identical side dividers, with in the center a open space; side dividers 1.810 in.Lg; center open space 1.120 in.From the center open space to the botton of the panel 0.620 in.H;

N/a			
Unit	Of	Meas	ure

Shelf Life:

Demilitarization:

No