

View Online at <https://aerobasegroup.com/nsn/2520-01-474-3901>

**Hole Diameter:**

Between 0.430 inches and 0.450 inches

**Overall Length:**

Between 29.770 inches and 30.240 inches

**End Application:**

Nsn 2320-01-412-0143 truck, utility - hum-v

**Flange Outside Diameter:**

Between 2.948 inches and 2.952 inches

**First End Spline Length:**

Between 3.210 inches and 3.250 inches

**Second End Spline Length:**

Between 3.210 inches and 3.250 inches

**Second End Spline Minor Diameter:**

1.282 inches

**Second End Spline Major Diameter:**

1.375 inches

**Second End Pitch Diameter:**

Between 0.071 inches and 0.073 inches

**Err Default:**

Err default

**First End Type:**

Flanged

**Second End Type:**

Splined

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Err Default:**

Err default

**Err Default:**

Err default

**Second End Spline Type:**

Involute

**Second End Spline Pressure Angle In Deg:**

45.0

**Flangethickness:**

Between 0.303 inches and 0.355 inches

**Flange Thickness At Mounting Hole:**

Between 0.180 inches and 0.200 inches

**Special Features:**

Item for right hand only; surface hardness rockwell c 58-63 - core hardness rockwell c 35 max; mat'l for boot clamp - stainless steel, type 304 iaw astm a167

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T306-d