

View Online at <https://aerobasegroup.com/nsn/2520-01-474-4012>

Hole Diameter:

Between 0.430 inches and 0.450 inches

Overall Length:

Between 25.000 inches and 25.470 inches

End Application:

Nsn 2320-01-412-0143 truck, utility - hum-v

Flange Outside Diameter:

Between 2.948 inches and 2.952 inches

First End Spline Length:

Between 3.210 inches and 3.250 inches

Second End Spline Length:

Between 3.210 inches and 3.250 inches

Second End Spline Minor Diameter:

1.282 inches

Second End Spline Major Diameter:

1.375 inches

Second End Pitch Diameter:

Between 0.071 inches and 0.073 inches

Err Default:

Err default

First End Type:

Flanged

Second End Type:

Splined

Mounting Facility Type And Quantity:

6 unthreaded hole

Err Default:

Err default

Err Default:

Err default

Second End Spline Type:

Involute

Second End Spline Pressure Angle In Deg:

45.0

Flangethickness:

Between 0.303 inches and 0.355 inches

Flange Thickness At Mounting Hole:

Between 0.180 inches and 0.200 inches

Special Features:

Item for left hand only; surface hardness rockwell c 58-63 - core hardness rockwell c 35 max; mat'l for boot clamp - stainless steel, type 304 iaw astm a167

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T306-d