

View Online at <https://aerobasegroup.com/nsn/2530-00-063-1358>

**Groove Depth:**

Between 0.741 inches and 0.811 inches

**Overall Length:**

Between 3.656 inches and 3.718 inches

**Overall Width:**

4.130 inches

**Bearing Surface Width:**

0.750 inches

**Rim Style:**

Curved base

**Design Type:**

Divided wheel

**Design Form:**

Disk

**Hub:**

Included

**Bearings:**

Included

**Mounting Type For Which Designed:**

Single tire

**Bearing Quantity:**

1

**Bearing Inside Diameter:**

1.250 inches

**Hole Location:**

Located in center of rim

**Disk Type:**

Double

**Lightening Hole:**

Not included

**Bearing Type:**

Roller

**Valve Hole Shape:**

Round

**Tire Rim Diameter:**

6.000 inches

**Tire:**

Not included

**Hub Characteristic:**

Demountable

**Lubrication Fitting:**

Not provided

**Axle Recess Diameter:**

Between 1.594 inches and 2.094 inches

**Sand Band Recess Diameter:**

Between 2.499 inches and 2.501 inches

**Bearing Recess Diameter:**

Between 2.062 inches and 2.094 inches

**Sand Band Recess Depth:**

0.500 inches

**Bearing Recess Depth:**

Between 0.875 inches and 1.3125 inches

**Hub Style:**

Double recess straight

**Special Features:**

Bearing recess diameter 2.4395 in. Min, 2.4405 in. Maximum flange end if cast iron or steel, 2.4376 in. Min, 2.4386 in. Maximum flange end if aluminum, 1.9365 in. Min, 1.9375 in. Maximum other end if cast iron or steel, 1.9351 in. Min, 1.9361 in. Maximum other end if aluminum, metal thickness 0.897 if steel, 0.0910 if aluminum

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T307-s