

View Online at <https://aerobasegroup.com/nsn/2530-00-063-1358>

Groove Depth:

Between 0.741 inches and 0.811 inches

Overall Length:

Between 3.656 inches and 3.718 inches

Overall Width:

4.130 inches

Bearing Surface Width:

0.750 inches

Rim Style:

Curved base

Design Type:

Divided wheel

Design Form:

Disk

Hub:

Included

Bearings:

Included

Mounting Type For Which Designed:

Single tire

Bearing Quantity:

1

Bearing Inside Diameter:

1.250 inches

Hole Location:

Located in center of rim

Disk Type:

Double

Lightening Hole:

Not included

Bearing Type:

Roller

Valve Hole Shape:

Round

Tire Rim Diameter:

6.000 inches

Tire:

Not included

Hub Characteristic:

Demountable

Lubrication Fitting:

Not provided

Axle Recess Diameter:

Between 1.594 inches and 2.094 inches

Sand Band Recess Diameter:

Between 2.499 inches and 2.501 inches

Bearing Recess Diameter:

Between 2.062 inches and 2.094 inches

Sand Band Recess Depth:

0.500 inches

Bearing Recess Depth:

Between 0.875 inches and 1.3125 inches

Hub Style:

Double recess straight

Special Features:

Bearing recess diameter 2.4395 in. Min, 2.4405 in. Maximum flange end if cast iron or steel, 2.4376 in. Min, 2.4386 in. Maximum flange end if aluminum, 1.9365 in. Min, 1.9375 in. Maximum other end if cast iron or steel, 1.9351 in. Min, 1.9361 in. Maximum other end if aluminum, metal thickness 0.897 if steel, 0.0910 if aluminum

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T307-s