

View Online at <https://aerobasegroup.com/nsn/2530-00-066-1485>

Tread Pattern:

Smooth tread

Overall Length:

Between 5.156 inches and 5.219 inches

Mounting Feature Diameter:

Between 2.4385 inches and 2.4395 inches

Bearing Surface Width:

0.8750 inches

Size Designator:

21 by 3 by 6

Load Capacity:

1800.000 pounds

Tire Type:

Solid, flat cushion tread

Design Type:

Solid cast disk

Hub:

Included

Rim:

Included

Bearings:

Included

Bearing Quantity:

1

Bearing Inside Diameter:

Between 1.2790 inches and 1.6255 inches

Bearing Type:

Tapered roller

Tire:

Included

Hub Cap Mounting Feature:

Included

Hub Cap:

Included

Hub Characteristic:

Integral

Rim Characteristic:

Integral

Integral Rim Type:

Flat base

Lubrication Fitting:

Not provided

Tire Characteristic:

Integral

Tire Arrangement Characteristic:

Single

Axle Recess Major Diameter:

Between 2.625 inches and 2.656 inches

Axle Recess Minor Diameter:

Between 2.063 inches and 2.094 inches

Sand Band Recess Diameter:

Between 3.061 inches and 3.063 inches

Sand Band Recess Depth:

Between 0.562 inches and 0.564 inches

Special Features:

Bearing recess depth 1.438 in. Depth of flange end bearing recess, 0.875 in. Depth of other end bearing recess

Material:

Aluminum

Material:

Aluminum

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T307-t