## NSN 2530-00-289-7402

Solid Rubber Tire Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-289-7402 **Tread Pattern:** Smooth tread **Overall Length:** 2.750 inches **Mounting Hole Diameter:** Any acceptable **Mounting Hole Quantity: Bearing Surface Width:** 2.750 inches **Mounting Bolt Circle Diameter:** Any acceptable **Pilot Hole Diameter:** Any acceptable Size Designator: 8 by 2-1/2 in. **Load Capacity:** 560.000 pounds Tire Type: Solid, flat cushion tread **Design Type:** Solid cast disk **Hub:** Not included Rim: Not included Bearings: Included Wheel Diameter: 6.750 inches **Bearing Quantity: Bearing Inside Diameter:** 1.000 inches **Bearing Type:** Roller

Tire: Included **Hub Cap Mounting Feature:** Not included Wheel Width At Outside Diameter: 2.500 inches

## NSN 2530-00-289-7402

Solid Rubber Tire Wheel - Page 2 of 2



Hub Characteristic:
Integral
Hub Style:
3
Lubrication Fitting:
Not provided
Rim Type For Which Designed:
Pressed-on
Tire Characteristic:
Integral
Tire Arrangement Characteristic:
Single
Offset Distance From Rim Centerline To Outside Of Wheel Mounting:
Any acceptable
Axle Recess Diameter:
1.688 inches
Hub Style:
Straight
Material:
Aluminum
Material:
Aluminum
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T307-t