NSN 2530-00-294-7207

Friction Lining - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2530-00-294-7207

Fabrication Method:
Molded
Width:
Between 3.984 inches and 4.016 inches
Minor Thickness:
0.578 inches
Major Thickness:
0.750 inches
Hole Arrangement Style:
Indefinite
Strengthening Feature:
Interwoven wire
Friction Lining Material:
Asbestos composition
Lining Style:
Segment tapered
Arc Length:
9.688 inches
Minor Radius:
8.000 inches
Application Type:
Application Type.
Dry
Dry
Dry Hole Type And Quantity:
Dry Hole Type And Quantity: 8 counterbored
Dry Hole Type And Quantity: 8 counterbored Features Provided:
Dry Hole Type And Quantity: 8 counterbored Features Provided: Rigid friction lining
Dry Hole Type And Quantity: 8 counterbored Features Provided: Rigid friction lining Surface Condition And Location:
Dry Hole Type And Quantity: 8 counterbored Features Provided: Rigid friction lining Surface Condition And Location: One side ground
Dry Hole Type And Quantity: 8 counterbored Features Provided: Rigid friction lining Surface Condition And Location: One side ground Attachment Method:
Dry Hole Type And Quantity: 8 counterbored Features Provided: Rigid friction lining Surface Condition And Location: One side ground Attachment Method: Riveted
Dry Hole Type And Quantity: 8 counterbored Features Provided: Rigid friction lining Surface Condition And Location: One side ground Attachment Method: Riveted Special Features:
Dry Hole Type And Quantity: 8 counterbored Features Provided: Rigid friction lining Surface Condition And Location: One side ground Attachment Method: Riveted Special Features: Ounterbore on outer arc
Dry Hole Type And Quantity: 8 counterbored Features Provided: Rigid friction lining Surface Condition And Location: One side ground Attachment Method: Riveted Special Features: Ounterbore on outer arc Shelf Life:
Hole Type And Quantity: 8 counterbored Features Provided: Rigid friction lining Surface Condition And Location: One side ground Attachment Method: Riveted Special Features: Ounterbore on outer arc Shelf Life: N/a
Hole Type And Quantity: 8 counterbored Features Provided: Rigid friction lining Surface Condition And Location: One side ground Attachment Method: Riveted Special Features: Ounterbore on outer arc Shelf Life: N/a
Hole Type And Quantity: 8 counterbored Features Provided: Rigid friction lining Surface Condition And Location: One side ground Attachment Method: Riveted Special Features: Ounterbore on outer arc Shelf Life: N/a Unit Of Measure:
Dry Hole Type And Quantity: 8 counterbored Features Provided: Rigid friction lining Surface Condition And Location: One side ground Attachment Method: Riveted Special Features: Ounterbore on outer arc Shelf Life: N/a Unit Of Measure: Demilitarization: