Tandem Axle Torque Rod - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2530-00-311-7529

Thread Direction:Right-handThread Length:1.188 inchesDiameter:1.250 inchesTaper Length:Between 1.772 inches and 1.822 inchesTaper Major Diameter:1.317 inchesThread Size:1-14Distance Between Mounting Facility Centers:Between 22.906 inches and 22.969 inchesScrew Thread Series Designator:UnfAdjustability:NonadjustableEnd Type:Ball stud
Thread Length:1.188 inchesDiameter:1.250 inchesTaper Length:Between 1.772 inches and 1.822 inchesTaper Major Diameter:1.317 inchesThread Size:1-14Distance Between Mounting Facility Centers:Between 22.906 inches and 22.969 inchesScrew Thread Series Designator:UnfAdjustability:NonadjustableEnd Type:Ball stud
1.188 inchesDiameter:1.250 inchesTaper Length:Between 1.772 inches and 1.822 inchesTaper Major Diameter:1.317 inchesThread Size:1.14Distance Between Mounting Facility Centers:Between 22.906 inches and 22.969 inchesScrew Thread Series Designator:UnfAdjustability:NonadjustableEnd Type:Ball stud
Diameter:1.250 inchesTaper Length:Between 1.772 inches and 1.822 inchesTaper Major Diameter:1.317 inchesThread Size:1-14Distance Between Mounting Facility Centers:Between 22.906 inches and 22.969 inchesScrew Thread Series Designator:UnfAdjustability:NonadjustableEnd Type:Ball stud
1.250 inches Taper Length: Between 1.772 inches and 1.822 inches Taper Major Diameter: 1.317 inches Thread Size: 1.14 Distance Between Mounting Facility Centers: Between 22.906 inches and 22.969 inches Screw Thread Series Designator: Unf Adjustability: Nonadjustable End Type: Ball stud
Taper Length:Between 1.772 inches and 1.822 inchesTaper Major Diameter:1.317 inchesThread Size:1-14Distance Between Mounting Facility Centers:Between 22.906 inches and 22.969 inchesScrew Thread Series Designator:UnfAdjustability:NonadjustableEnd Type:Ball stud
Between 1.772 inches and 1.822 inches Taper Major Diameter: 1.317 inches Thread Size: 1-14 Distance Between Mounting Facility Centers: Between 22.906 inches and 22.969 inches Screw Thread Series Designator: Unf Adjustability: Nonadjustable End Type: Ball stud
Taper Major Diameter:1.317 inchesThread Size:1-14Distance Between Mounting Facility Centers:Between 22.906 inches and 22.969 inchesScrew Thread Series Designator:UnfAdjustability:NonadjustableEnd Type:Ball stud
1.317 inches Thread Size: 1-14 Distance Between Mounting Facility Centers: Between 22.906 inches and 22.969 inches Screw Thread Series Designator: Unf Adjustability: Nonadjustable End Type: Ball stud
Thread Size:1-14Distance Between Mounting Facility Centers:Between 22.906 inches and 22.969 inchesScrew Thread Series Designator:UnfAdjustability:NonadjustableEnd Type:Ball stud
1-14 Distance Between Mounting Facility Centers: Between 22.906 inches and 22.969 inches Screw Thread Series Designator: Unf Adjustability: Nonadjustable End Type: Ball stud
Distance Between Mounting Facility Centers: Between 22.906 inches and 22.969 inches Screw Thread Series Designator: Unf Adjustability: Nonadjustable End Type: Ball stud
Between 22.906 inches and 22.969 inches Screw Thread Series Designator: Unf Adjustability: Nonadjustable End Type: Ball stud
Screw Thread Series Designator: Unf Adjustability: Nonadjustable End Type: Ball stud
Unf Adjustability: Nonadjustable End Type: Ball stud
Adjustability: Nonadjustable End Type: Ball stud
Nonadjustable End Type: Ball stud
End Type: Ball stud
Ball stud
Ball Stud Location:
Both ends
Taper:
1.000 per foot in inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T307-f