NSN 2530-00-358-9546

Wheel Spindle Kingpin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2530-00-358-9546

| O colored attacks to the day |
|--|
| Casehardening Indicator: |
| Casehardened |
| Width: |
| 0.500 inches |
| Diameter: |
| Between 1.5003 inches and 1.5008 inches |
| Length: |
| 7.469 inches |
| Depth: |
| 0.0538 inches |
| Metallic Hardness Rating: |
| 59.0 rockwell c and 64.0 rockwell c |
| Retaining Device Type: |
| Lockpin slot |
| Distance From Nearest End To Groove/slot Center: |
| 1.875 inches |
| Center To Center Distance Between Groove/slot: |
| 2.813 inches |
| Threaded Securing End: |
| Not included |
| Screwdriver Slotted End: |
| Not included |
| Lubrication Fitting Threaded Hole: |
| Not included |
| Special Features: |
| Both ends chamfered, 1/16 in. Lg chamfer, 30 degrees chamfer |
| Material: |
| Steel, sae 8620 |
| Material: |
| Steel comp 8620 |
| Material Specification: |
| Sae 8620 assn standard 1st material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T307-n |