## NSN 2530-00-409-8766

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-409-8766 **Body Material:** Any acceptable First End Outside Diameter: 0.875 inches **Tempurature Rating:** Not rated **Overall Height:** 3.031 inches **Overall Width:** 2.375 inches **Bore Diameter:** 2.000 inches Seat Angle In Deg: Any acceptable **Mounting Facility Thread Class: Mounting Facility Thread Direction:** Right-hand First End External Thread Length: 1.500 inches **Compressed Length:** 23.375 inches **Extended Length:** 27.625 inches **Pressure Rating:** Not rated **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: First Piston Rod End Thread Diameter: 0.875 inches First Piston Rod End Thready Qty Per Inch (tpi): First Piston Rod End Thread Class: 2a First Piston Rod End Thread Direction:

Right-hand
Piston Rod End Similarity:

Identical

## NSN 2530-00-409-8766

Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Type And Location:
Stud cylinder head end
Port Location And Quantity:
1 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Unf
Port Thread Diameter:
0.750 inches
Port Thready Qty Per Inch (tpi):
16
Port Thread Class:
2b
Fsc Application Data:
Steering, gear, vehicular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A34200