NSN 2530-00-422-9354

Master Hydraulic Brake Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-422-9354 **Body Material:** Any acceptable **Mounting Provision:** Threaded mounting holes **Tempurature Rating:** Not rated **Overall Height:** 5.750 inches **Overall Width:** 3.875 inches **Bore Diameter:** 1.750 inches **Longest Horizontal Distance Between Mounting Centers:** 4.750 inches **Shortest Horizontal Distance Between Mounting Centers:** 2.375 inches **Longest Vertical Distance Between Mounting Centers:** 2.750 inches **Actuation Method:** Direct **End Application:** 3805-00-075-3312 Seat Angle In Deg: Any acceptable **Mounting Facility Thread Class:** 2b **Mounting Facility Thread Direction:** Right-hand Compressed Length: 9.531 inches **Extended Length:** 9.531 inches **Mounting Provision Arrangement Style:** Three hole triangular **Reservoir Type:** Integral **Straight Bore Inside Diameter:** 1.750 inches **Features Provided:**

Mounting Facility Thread Series Designator:Unf

Filler plug

NSN 2530-00-422-9354

Master Hydraulic Brake Cylinder Assembly - Page 2 of 2



Mounting Facility Thread Diameter:
0.438 inches
Mounting Facility Thready Qty Per Inch (tpi):
20
Mounting Type And Location:
Flange center section
Mounting Facility Thread Length:
0.625 inches
Port Location And Quantity:
3 cylinder head end
Port Style:
Gasket seal
Port Thread Series Designator:
Unf
Port Thread Diameter:
0.500 inches
Port Thready Qty Per Inch (tpi):
20
Port Thread Class:
2b
Bleeding Feature Quantity:
1
Stoplight Switch Thread Series Designator:
Npt
Stoplight Switch Thready Qty Per Inch (tpi):
27
Stoplight Switch Pipe Thread Size:
0.125 inches
Special Features:
Indentical mounting provisions on both left and rightside
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A34200