Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-432-1794

Body Material:SteelFirst End Outside Diameter:0.970 inchesOverall Height:6.000 inchesOverall Width:3.500 inchesBore Diameter:2.500 inchesFirst End Hole Diameter:0.565 inchesFirst End Thickness At Mounting Holes:1.000 inchesCompressed Length:11.000 inchesExtended Length:14.375 inchesFeatures Provided:Cushioned strokeIntegral Valve Operation Method:Mechanical
First End Outside Diameter:0.970 inchesOverall Height:6.000 inchesOverall Width:3.500 inchesBore Diameter:2.500 inchesFirst End Hole Diameter:0.565 inchesFirst End Thickness At Mounting Holes:1.000 inchesCompressed Length:11.000 inchesExtended Length:14.375 inchesFeatures Provided:Cushioned strokeIntegral Valve Operation Method:
0.970 inches Overall Height: 6.000 inches Overall Width: 3.500 inches Bore Diameter: 2.500 inches First End Hole Diameter: 0.565 inches First End Thickness At Mounting Holes: 1.000 inches Compressed Length: 11.000 inches Extended Length: 14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
Overall Height:6.000 inchesOverall Width:3.500 inchesBore Diameter:2.500 inchesFirst End Hole Diameter:0.565 inchesFirst End Thickness At Mounting Holes:1.000 inchesCompressed Length:11.000 inchesExtended Length:14.375 inchesFeatures Provided:Cushioned strokeIntegral Valve Operation Method:
6.000 inches Overall Width: 3.500 inches Bore Diameter: 2.500 inches First End Hole Diameter: 0.565 inches First End Thickness At Mounting Holes: 1.000 inches Compressed Length: 11.000 inches Extended Length: 14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
Overall Width: 3.500 inches Bore Diameter: 2.500 inches First End Hole Diameter: 0.565 inches First End Thickness At Mounting Holes: 1.000 inches Compressed Length: 11.000 inches Extended Length: 14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
3.500 inches Bore Diameter: 2.500 inches First End Hole Diameter: 0.565 inches First End Thickness At Mounting Holes: 1.000 inches Compressed Length: 11.000 inches Extended Length: 14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
Bore Diameter: 2.500 inches First End Hole Diameter: 0.565 inches First End Thickness At Mounting Holes: 1.000 inches Compressed Length: 11.000 inches Extended Length: 14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
2.500 inches First End Hole Diameter: 0.565 inches First End Thickness At Mounting Holes: 1.000 inches Compressed Length: 11.000 inches Extended Length: 14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
First End Hole Diameter: 0.565 inches First End Thickness At Mounting Holes: 1.000 inches Compressed Length: 11.000 inches Extended Length: 14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
0.565 inches First End Thickness At Mounting Holes: 1.000 inches Compressed Length: 11.000 inches Extended Length: 14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
First End Thickness At Mounting Holes: 1.000 inches Compressed Length: 11.000 inches Extended Length: 14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
1.000 inches Compressed Length: 11.000 inches Extended Length: 14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
Compressed Length: 11.000 inches Extended Length: 14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
11.000 inches Extended Length: 14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
Extended Length: 14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
14.375 inches Features Provided: Cushioned stroke Integral Valve Operation Method:
Features Provided: Cushioned stroke Integral Valve Operation Method:
Cushioned stroke Integral Valve Operation Method:
Integral Valve Operation Method:
-
Mechanical
Design Characteristics:
Double acting single cylinder
First Piston Rod End Style:
Ring type
Mounting Type And Location:
Fork cylinder head end
Port Location And Quantity:
2 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Unf
Port Thread Diameter:
0.562 inches
Port Thready Qty Per Inch (tpi):
18
Port Thread Class:
2b
Shelf Life:
N/a

Linear Actuating Cylinder Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A34200