## NSN 2530-00-470-6424

Friction Lining - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2530-00-470-6424

| Fabrication Method:   |
|---|
| Molded  |
| Width:  |
| 4.000 inches  |
| Thickness:  |
| 0.750 inches  |
| Hole Arrangement Style:   |
| Double even   |
| Strengthening Feature:  |
| Internally molded-in reinforcement  |
| Lining Style:   |
| Segment plain   |
| Arc Length:   |
| 9.500 inches  |
| Minor Radius:   |
| 7.875 inches  |
| Application Type:   |
| Dry   |
| Hole Type And Quantity:   |
| 8 counterbored  |
| Features Provided:  |
| Rigid friction lining   |
| Surface Condition And Location:   |
| One side ground   |
| Attachment Method:  |
| Riveted   |
| Supplementary Features:   |
| This item has been reviewed for asbestos material; the current approved sources; 23382 have indicated their part number contained |
| asbestos prior to 1984; they continue to manufacture the same part number without asbestos material after 1984                    |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A230a0  |