

View Online at <https://aerobasegroup.com/nsn/2530-00-484-8453>

Body Material:

Steel

Mounting Provision:

Threaded mounting holes

Overall Height:

1.500 inches

Overall Width:

2.250 inches

Bore Diameter:

0.812 inches

End Application:

Nimitz class cvn. Landing craft air cushion (lcac). C-2a reprocured aircraft. Ah-1w advance attack, hh-60j uscg search and rescue, hh-60h uscg search and resuce helicopters. Shipboard material handling equipment (mhe). Forrestal class cv.

Seat Angle In Deg:

37.0 single port

Mounting Facility Thread Class:

2b

Mounting Facility Thread Direction:

Right-hand

Bore Type:

Straight

Mounting Provision Arrangement Style:

Two hole

Mounting Position:

Left and right

Features Provided:

Rubber boot

Mounting Facility Thread Series Designator:

Unc

Mounting Facility Thread Diameter:

0.250 inches

Mounting Facility Thready Qty Per Inch (tpi):

20

Design Characteristics:

Single acting single cylinder

Mounting Type And Location:

Flange center section

Mounting Facility Thread Length:

0.475 inches

Center To Center Distance Between Mounting Provisions:

1.364 inches

Port Location And Quantity:

1 center section

Port Style:

Swivel nut, inverted flare single port

Port Thread Series Designator:

Unf single port

Port Thread Diameter:

0.375 inches single port

Port Thread Qty Per Inch (tpi):

24 single port

Port Thread Class:

2b single port

Bleeding Feature Quantity:

1

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A34200