
## NSN 2530-00-603-5768

Pneumatic Tire Wheel - Page 1 of 2





Groove Depth: 1.600 inches **Overall Width:** 8.926 inches Mounting Hole Diameter: Between 1.210 inches and 1.220 inches Mounting Hole Quantity: 10 **Ring Style:** Rim side ring slotted **Effective Width:** 7.562 inches Mounting Bolt Circle Diameter: Between 11.243 inches and 11.257 inches **Pilot Hole Diameter:** Between 8.725 inches and 8.729 inches Design Type: Integral rim **Design Form:** Disk Hub: Not included **Bearings:** Not included Ring: Included Mounting Type For Which Designed: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted **Tire Rim Diameter:** 20.000 inches Tire: Not included Mounting Face Type: Convex Offset Distance From Rim Centerline To Outside Wheel Mounting Face:

6.813 inches

## NSN 2530-00-603-5768

Pneumatic Tire Wheel - Page 2 of 2



Ring Type For Which Designed: Side **Bolt/stud Mounting Facility:** Not included Hub Characteristic: Demountable Lightening Hole Quantity: 5 Lightening Hole Hub Cap Mounting Feature: Not included Wheel Assembly National Stock Number: 2530-01-506-7244 **Fsc Application Data:** Wheels, vehicular Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T307-s