NSN 2530-00-621-0709

Between 8.802 inches and 8.812 inches

Tread Pattern:
Smooth tread
Overall Length:

Size Designator: 16 by 4 by 7-1/2 Load Capacity:

Solid Rubber Tire Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-621-0709

Not rated
Tire Type:
Solid, flat tread
Design Type:
Stamped disk
Hub:
Included
Rim:
Included
Bearings:
Not included
Tire:
Included
Hub Cap Mounting Feature:
Not included
Hub Characteristic:
Integral
Hub Style:
5
Rim Characteristic:
Demountable
Demountable Rim Type:
Pressed-on
Lubrication Fitting:
Provided
Tire Characteristic:
Integral
Tire Arrangement Characteristic:
Single
Axle Recess Diameter:
Between 4.297 inches and 4.375 inches
Sand Band Recess Diameter:
Between 4.998 inches and 5.000 inches
Bearing Recess Diameter:
Between 1.125 inches and 4.874 inches

NSN 2530-00-621-0709

Solid Rubber Tire Wheel - Page 2 of 2



Sand Band Recess Depth:

1.125 inches

Bearing Recess Depth:

Between 2.990 inches and 3.000 inches

Hub Style:

Double recess straight

Material:

Any acceptable

Fsc Application Data:

Suspension, track, vehicular

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

T307-t