## NSN 2530-00-640-3327

Solid Rubber Tire Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-640-3327 **Tread Pattern:** Smooth tread **Overall Length:** 2.813 inches **Bearing Surface Width:** 0.7813 inches Size Designator: 8 by 3/4 by 2 **Load Capacity:** 640.000 pounds Tire Type: Solid, flat cushion tread **Design Type:** Solid cast disk Hub: Included Rim: Not included Bearings: Included Wheel Diameter: 8.000 inches **Bearing Quantity: Bearing Inside Diameter:** 0.750 inches **Bearing Type:** Tapered roller Tire: Included **Hub Cap Mounting Feature:** Not included Wheel Width At Outside Diameter: 2.000 inches **Hub Characteristic:** Integral **Hub Style:** 3 **Lubrication Fitting:** Not provided **Rim Type For Which Designed:** 

Pressed-on

## **NSN 2530-00-640-3327**Solid Rubber Tire Wheel - Page 2 of 2



| Tire Characteristic:            |
|---------------------------------|
| Integral                        |
| Tire Arrangement Characteristic |
| Single                          |
| Axle Recess Diameter:           |
| 0.750 inches                    |
| Hub Style:                      |
| Straight                        |
| Material:                       |
| Aluminum alloy                  |
| Material:                       |
| Aluminum alloy                  |
| Fsc Application Data:           |
| Trailer, aircraft, engine       |
| Shelf Life:                     |
| N/a                             |
| Unit Of Measure:                |
|                                 |
| Demilitarization:               |
| No                              |
| Fiig:                           |
| T307-t                          |
|                                 |