NSN 2530-00-659-6952

Master Hydraulic Brake Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-659-6952

| Body Material: |
|--|
| Iron, cast |
| First End Outside Diameter: |
| Any acceptable |
| Mounting Provision: |
| Unthreaded mounting holes |
| Tempurature Rating: |
| Not rated |
| Overall Height: |
| 3.969 inches |
| Overall Width: |
| 2.250 inches |
| Bore Diameter: |
| 0.750 inches |
| Actuation Method: |
| Direct |
| First End External Thread Length: |
| Any acceptable |
| Compressed Length: |
| 5.969 inches |
| Extended Length: |
| 7.219 inches |
| Mounting Provision Arrangement Style: |
| Two hole |
| Reservoir Type: |
| Integral |
| Straight Bore Inside Diameter: |
| 0.750 inches |
| Features Provided: |
| Rubber boot |
| First End Tongue Length: |
| 0.625 inches |
| First Piston Rod End Style: |
| External threaded |
| First Piston Rod End Thread Series Designator: |
| Unc |
| First Piston Rod End Thread Diameter: |
| 0.312 inches |
| First Piston Rod End Thready Qty Per Inch (tpi): |
| 18 |

First Piston Rod End Thread Class:

NSN 2530-00-659-6952

Master Hydraulic Brake Cylinder Assembly - Page 2 of 2



| First Piston Rod End Thread Direction: |
|--|
| Right-hand |
| Mounting Type And Location: |
| Flange center section |
| Mounting Facility Diameter: |
| 0.391 inches |
| Center To Center Distance Between Mounting Provisions: |
| 3.438 inches |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A34200