NSN 2530-00-679-7922

Solid Rubber Tire Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-679-7922

Tread Pattern:

Smooth tread

Mounting Hole Diameter:

0.500 inches

Mounting Hole Quantity:

6

Mounting Bolt Circle Diameter:

6.500 inches

End Application:

2530-00-679-7922

Pilot Hole Diameter:

2.0 inches

Size Designator:

23 by 3

Load Capacity:

2.0 kilograms

Tire Type:

Solid, flat tread

Design Type:

Solid cast disk

Hub:

Not included

Rim:

Included

Bearings:

Not included

Tire:

Included

Hub Cap Mounting Feature:

Not included

Hub Characteristic:

Demountable

Rim Characteristic:

Integral

Integral Rim Type:

Flat base

Tire Characteristic:

Demountable

Tire Arrangement Characteristic:

Single

Offset Distance From Rim Centerline To Outside Of Wheel Mounting:

1.750 inches

NSN 2530-00-679-7922

Solid Rubber Tire Wheel - Page 2 of 2



Material:

Aluminum

Material:

Aluminum

Fsc Application Data:

Track suspension, guided missile loader

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T307-t