NSN 2530-00-699-7849

Solid Rubber Tire Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-699-7849

Tread Pattern: Smooth tread Mounting Hole Diameter: Between 0.469 inches and 0.485 inches Mounting Bolt Circle Diameter: 6 Mounting Bolt Circle Diameter: 4.438 inches Pilot Hole Diameter: Between 4.005 inches and 4.015 inches Size Designator: 12 by 2-15/32 by 10 Tire Type: Solid, crowned cushion tread Design Type: Solid cast disk Hub: Not included Bearings: Not included Wheel Diameter: 10.000 inches Tire: 10.000 inches Tire: Included Hub Cap Mounting Feature: Not included Wheel Width At Outside Diameter: 3.219 inches Hub Characteristic: Integral Tire Arrangement Characteristic: Integral Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: Naterial:	
Houting Hole Diameter: Between 0.469 inches and 0.485 inches Mouting Hole Quantity: 6 Mouting Bolt Circle Diameter: 4.438 inches Pilot Hole Diameter: Between 4.005 inches and 4.015 inches Size Designator: 12 by 2.15/32 by 10 Tire Type: Solid, card disk Hub: Not included Remin: Not included Bearings: Not included Phee Diameter: 10.000 inches Tire: 10.000 inches Tire: 10.000 inches Tire: 10.000 inches Tire: Not included Hub Cap Mounting Feature: Not included Hub Characteristic: 3.219 inches Hub Characteristic: Integral Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting reacteristic: Single Pire Distance From Rim Centerline To Outside Of Wheel Mounting reacteristi	Tread Pattern:
Between 0.469 inches and 0.485 inches Mounting Hole Quantity: 6 Mounting Bolt Circle Diameter: 4.438 inches Pilot Hole Diameter: Between 4.005 inches and 4.015 inches Size Designator: 12 by 2-15/32 by 10 Tire Type: Solid, crowned cushion tread Design Type: Solid cast disk Hub: Not included Bearings: Not included Bearings: Not included Hub: 10.000 inches Tire: 10.000 inches Tire: 10.000 inches Pilot Hot At Outside Diameter: 3.219 inches Hub Characteristic: Integral Tire Characteristic: Integral Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Material: Steel	Smooth tread
Hounting Hole Quantity:6Hounting Bolt Circle Diameter:4.438 inchesPilot Hole Diameter:Between 4.005 inches and 4.015 inchesSize Designator:12 by 2-15/32 by 10Tire Type:Solid, crowned cushion treadDesign Type:Solid cast diskHub:NatioludedFilm:NatioludedBerings:NatioludedDisting:10:00 inchesTire:IncludedHub:NatioludedDesign Type:NatioludedBerings:NatioludedBerings:NatioludedHub:10:00 inchesTire:IncludedHub:NatioludedBering:NatioludedHub:IncludedHub:IncludedHub:IncludedHub:IncludedIncludedHub:Integral <tr< td=""><td>Mounting Hole Diameter:</td></tr<>	Mounting Hole Diameter:
6 Mounting Bolt Circle Diameter: 4.438 inches Pilot Hole Diameter: Between 4.005 inches and 4.015 inches Size Designator: 12 by 2-15/32 by 10 Tire Type: Solid, crowned cushion tread Design Type: Solid, crowned cushion tread Design Type: Solid cast disk Hub: Not included Bearings: Not included Bearings: Noto included Wheel Diameter: 10.000 inches Tire: Included Wheel Diameter: 10.000 inches Tire: Included Wheel Diameter: 10.000 inches Tire: Included Wheel Width At Outside Diameter: 3.219 inches Hub Characteristic: Integral Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Material: <t< td=""><td>Between 0.469 inches and 0.485 inches</td></t<>	Between 0.469 inches and 0.485 inches
Mounting Bolt Circle Diameter: 4.438 inches Pilot Hole Diameter: Between 4.005 inches and 4.015 inches Size Designator: 12 by 2-15/32 by 10 Tire Type: Solid, crowned cushion tread Design Type: Solid cast disk Hub: Not included Bearings: Not included Bearings: Not included Hub: Not included Bearings: Not included Bearings: Not included Hub: 10.000 inches Tire: Included Hub Characteristic: Not included Hub Characteristic: Included Hub Characteristic: Integral Tire Characteristic: Integral Cifset Distance From Rim Centerline To Outside Of Wheel Mounting: Intogral Directristic: Single Directristic: Single Direstance From Rim Centerline To Outside Of W	Mounting Hole Quantity:
4.438 inchesPilot Hole Diameter:Between 4.005 inches and 4.015 inchesSize Designator:12 by 2-15/32 by 10Tire Type:Solid, crowned cushion treadDesign Type:Solid, crowned cushion treadDesign Type:Solid cast diskHub:Not includedBearings:Not includedBearings:Not includedHube:10.000 inchesTire:IncludedHub:Not includedWheel Diameter:10.000 inchesTire:IncludedHub Characteristic:IncludedHub Characteristic:IntegralTire Arrangement Characteristic:SingleOffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesKaterial:Single <td>6</td>	6
Pilot Hole Diameter:Between 4.005 inches and 4.015 inchesSize Designator:12 by 2-15/32 by 10Tire Type:Solid, crowned cushion treadDesign Type:Solid cast diskHub:Not includedBearings:Not includedWheel Diameter:10:000 inchesTire:IncludedHub:Not includedWheel Diameter:10:000 inchesTire:IncludedHub Cap Mounting Feature:Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Characteristic:SingleOtifset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesKaterial:Single	Mounting Bolt Circle Diameter:
Between 4.005 inches and 4.015 inches Size Designator: 12 by 2-15/32 by 10 Tire Type: Solid, crowned cushion tread Design Type: Solid cast disk Hub: Not included Rim: Not included Bearings: Not included Bearings: Not included Hub Capenter: 10:000 inches Tire: Included Hub Cap Mounting Feature: Not included Hub Cap Mounting Feature: Not included Hub Characteristic: 10:000 inches Tire Characteristic: Integral Tire Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Hub Characteristic: Single	4.438 inches
Size Designator: 12 by 2-15/32 by 10 Tire Type: Solid, crowned cushion tread Design Type: Solid cast disk Hub: Not included Rim: Not included Bearings: Not included Bearings: Not included Wheel Diameter: 10.000 inches Tire: Included Hub Cap Mounting Feature: Not included Wheel Width At Outside Diameter: 3.219 inches Hub Characteristic: Integral Tire Characteristic: Integral Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches	Pilot Hole Diameter:
12 by 2-15/32 by 10Tire Type:Solid, crowned cushion treadDesign Type:Solid cast diskHub:Not includedRim:Not includedBearings:Not includedWheel Diameter:10.000 inchesTire:IncludedWheel Diameter:Not includedBuringUire10.000 inchesTire:IncludedHub Cap Mounting Feature:Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Arrangement Characteristic:SingleOffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesBaterial:Steel	Between 4.005 inches and 4.015 inches
Tire Type:Solid, crowned cushion treadDesign Type:Solid cast diskHub:Not includedRim:Not includedBearings:Not includedWheel Diameter:10.000 inchesTire:IncludedHub Cap Mounting Feature:Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Arrangement Characteristic:SingleOffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesSteel	Size Designator:
Solid, crowned cushion treadDesign Type:Solid cast diskHub:Not includedRim:Not includedBearings:Not includedWheel Diameter:10.000 inchesTire:IncludedNot includedHub:Wheel Diameter:10.000 inchesTire:IncludedHub Cap Mounting Feature:Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Characteristic:SingleOffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesMaterial:Steel	12 by 2-15/32 by 10
Design Type:Solid cast diskHub:Not includedRim:Not includedBearings:Not includedBearings:Not includedWheel Diameter:10.000 inchesTire:IncludedHub Cap Mounting Feature:Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Arrangement Characteristic:SingleOffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesBaterial:Steel	Тіге Туре:
Solid cast disk Hub: Not included Rim: Not included Bearings: Not included Wheel Diameter: 10.000 inches Tire: Included Hub Cap Mounting Feature: Not included Wheel Width At Outside Diameter: 3.219 inches Hub Characteristic: Integral Tire Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches	Solid, crowned cushion tread
Hub:Not includedRim:Not includedBearings:Not includedWheel Diameter:10.000 inchesTire:IncludedHub Cap Mounting Feature:Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Arrangement Characteristic:SingleOffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesMaterial:Steel	Design Type:
Not includedRim:Not includedBearings:Not includedWheel Diameter:Not includedWheel Diameter:10.000 inchesTire:IncludedHub Cap Mounting Feature:Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Characteristic:IntegralCiffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesMaterial:Steel	Solid cast disk
Rim:Not includedBearings:Not includedWheel Diameter:10.000 inchesTire:IncludedHub Cap Mounting Feature:Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Characteristic:SingleOffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesSteel	Hub:
Not includedBearings:Not includedWheel Diameter:10.000 inchesTire:IncludedHub Cap Mounting Feature:Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Characteristic:IntegralCifset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesMaterial:Steel	Not included
Bearings:Not includedWheel Diameter:10.000 inchesTire:IncludedHub Cap Mounting Feature:Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Characteristic:IntegralGiselOffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesMaterial:Steel	Rim:
Not includedWheel Diameter:10.000 inchesTire:IncludedHub Cap Mounting Feature:Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Characteristic:IntegralSingleOffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesMaterial:Steel	Not included
Wheel Diameter:10.000 inchesTire:IncludedHub Cap Mounting Feature:Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Characteristic:IntegralSingleOffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesMaterial:Steel	Bearings:
10.000 inches Tire: Included Hub Cap Mounting Feature: Not included Wheel Width At Outside Diameter: 3.219 inches Hub Characteristic: Integral Tire Characteristic: Integral Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Material: Steel	Not included
Tire:IncludedHub Cap Mounting Feature:Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Characteristic:IntegralTire Arrangement Characteristic:SingleOffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesMaterial:Steel	Wheel Diameter:
Included Hub Cap Mounting Feature: Not included Wheel Width At Outside Diameter: 3.219 inches Hub Characteristic: Integral Tire Characteristic: Integral Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Material: Steel	10.000 inches
Hub Cap Mounting Feature: Not included Wheel Width At Outside Diameter: 3.219 inches Hub Characteristic: Integral Tire Characteristic: Integral Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Material: Steel	Tire:
Not includedWheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Characteristic:IntegralTire Arrangement Characteristic:SingleOffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesMaterial:Steel	Included
Wheel Width At Outside Diameter:3.219 inchesHub Characteristic:IntegralTire Characteristic:IntegralTire Arrangement Characteristic:SingleOffset Distance From Rim Centerline To Outside Of Wheel Mounting:1.109 inchesMaterial:Steel	Hub Cap Mounting Feature:
3.219 inches Hub Characteristic: Integral Tire Characteristic: Integral Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Material: Steel	Not included
Hub Characteristic: Integral Tire Characteristic: Integral Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Material: Steel	Wheel Width At Outside Diameter:
Integral Tire Characteristic: Integral Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Material: Steel	3.219 inches
Tire Characteristic: Integral Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Material: Steel	Hub Characteristic:
Integral Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Material: Steel	Integral
Tire Arrangement Characteristic: Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Material: Steel	Tire Characteristic:
Single Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Material: Steel	Integral
Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 1.109 inches Material: Steel	Tire Arrangement Characteristic:
1.109 inches Material: Steel	Single
Material: Steel	Offset Distance From Rim Centerline To Outside Of Wheel Mounting:
Steel	1.109 inches
	Material:
Material:	Steel
	Material:
Steel	Steel

NSN 2530-00-699-7849

Solid Rubber Tire Wheel - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T307-t

