NSN 2530-00-700-1029

Pneumatic Tire Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-700-1029

1.500 inches Overall Width: 5.250 inches Mounting Hole Diameter: 1.281 inches Mounting Hole Quantity: 8 Effective Width: 5.000 inches Mounting Bolt Circle Diameter: 8.750 inches Pilot Hole Diameter: 8.750 inches Pilot Hole Diameter: Between 5.873 inches and 5.877 inches Rim Style: Flat lock Design Type: Integral rim Design Form: Disk Hub: Not included Bearings: Not included Bearings: Not included Bigle tre Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire: Not included Mounting Face Type: Concave	G	Groove Depth:
8.250 inches Mounting Hole Diameter: 1.281 inches Mounting Hole Quantity: 6 Effective Width: 5.000 inches Mounting Bolt Circle Diameter: 8.750 inches Pilot Hole Diameter: 8.750 inches Pilot Pilot Pilot Pilot: 9.750 inches Pilot Pilo	1	.500 inches
Mounting Hole Diameter: 1.281 inches Mounting Hole Quantity: 6 Effective Width: 5.000 inches Mounting Bolt Circle Diameter: 8.750 inches Pilot Hole Diameter: 9.750 inches Pilot Hole Diameter: 1.100 Conter 9.750 inches Pilot Hole Diameter: 9.750 Nich Designed: 1.101 Conter	C	Overall Width:
1.281 inches Mounting Hole Quantity: 6 Effective Width: 5.000 inches Mounting Bolt Circle Diameter: 8.750 inches Pilot Hole Diameter: Batween 5.873 inches and 5.877 inches Rim Style: Flat lock Design Type: Integral rim Design Form: Disk Hub: Not included Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20:000 inches Tire: Not included Mounting Face Type: Concave	6	.250 inches
Mounting Hole Quantity: 6 Effective Width: 5.000 inches Mounting Bolt Circle Diameter: 8.750 inches Pilot Hole Diameter: Between 5.873 inches and 5.877 inches Rim Style: Filat lock Design Type: Integral rim Design Form: Disk Hub: Not included Bearings: Not included Bearings: Not included Bearings: Not included Disk Type: Single tire Disk Type:	N	Iounting Hole Diameter:
S Effective Width: 5.000 inches Mounting Bolt Circle Diameter: 8.750 inches Pilot Hole Diameter: 8.750 inches Pilot Hole Diameter: Between 5.873 inches and 5.877 inches Rim Style: Flat lock Design Type: Integral rim Design Form: Disk Hub: Not included Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	1	.281 inches
Effective Width: 5.000 inches Mounting Bolt Circle Diameter: 8.750 inches Pilot Hole Diameter: Between 5.873 inches and 5.877 inches Rim Style: Flat lock Design Type: Flat lock Design Type: Integral rim Design Form: Disk Hub: Not included Bearings: Not included Bearings: Not included Mounting Type For Which Designed: Single tre Disk Type: Single tre Disk Type: Single tre Disk Type: Single Tire Disk Type: Single Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	N	Iounting Hole Quantity:
5.000 inches Mounting Bolt Circle Diameter: 8.750 inches Pilot Hole Diameter: Between 5.873 inches and 5.877 inches Rim Style: Flat lock Design Type: Flat lock Design Type: Integral rim Design Form: Disk Hub: Not included Bearings: Not included Bearings: Not included Mounting Type For Which Designed: Single tre Disk Type: Single tre Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included	6	
Mounting Bolt Circle Diameter: 8.750 inches Pilot Hole Diameter: Between 5.873 inches and 5.877 inches Rim Style: Flat lock Design Type: Flat lock Design Type: Integral rim Design Form: Disk Hub: Not included Bearings: Not included Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Songa Satter Satte	E	ffective Width:
Br50 inches Pilot Hole Diameter: Between 5.873 inches and 5.877 inches Rim Style: Flat lock Design Type: Flat lock Design Type: Integral rim Design Form: Disk Hub: Not included Bearings: Not included Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	5	.000 inches
Pilot Hole Diameter: Pilot Hole Diameter: Between 5.873 inches and 5.877 inches Rim Style: Flat lock Design Type: Integral rim Design Form: Disk Hub: Not included Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	Ν	Iounting Bolt Circle Diameter:
Between 5.873 inches and 5.877 inches Rim Style: Flat lock Design Type: Integral rim Design Form: Disk Hub: Not included Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	8	.750 inches
Rim Style: Flat lock Design Type: Integral rim Design Form: Disk Hub: Not included Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	F	ilot Hole Diameter:
Flat lock Design Type: Integral rim Design Form: Disk Hub: Not included Bearings: Not included Mounting Type For Which Designed: Single tre Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	E	Between 5.873 inches and 5.877 inches
Design Type: Integral rim Design Form: Disk Disk Hub: Not included Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type:	F	tim Style:
Integral rim Design Form: Disk Hub: Hub: Hub: Not included Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	F	lat lock
Design Form: Disk Hub: Not included Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	C	Design Type:
Disk Hub: Hub: Not included Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	h	ntegral rim
Hub: Not included Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	C	Design Form:
Not included Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	C	Disk
Bearings: Not included Mounting Type For Which Designed: Single tire Disk Type: Disk Type: Single Lightening Hole: Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type:	ŀ	lub:
Not included Mounting Type For Which Designed: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	Ν	lot included
Mounting Type For Which Designed: Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type:	E	Bearings:
Single tire Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	Ν	lot included
Disk Type: Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type:	N	Iounting Type For Which Designed:
Single Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type:	S	Single tire
Lightening Hole: Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type:	C)isk Type:
Included Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	S	Single
Valve Hole Shape: Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	L	ightening Hole:
Slotted Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	h	ncluded
Tire Rim Diameter: 20.000 inches Tire: Not included Mounting Face Type: Concave	۷	alve Hole Shape:
20.000 inches Tire: Not included Mounting Face Type: Concave	S	Slotted
Tire: Not included Mounting Face Type: Concave	Т	ire Rim Diameter:
Not included Mounting Face Type: Concave	2	0.000 inches
Mounting Face Type: Concave	Т	ïre:
Concave	Ν	lot included
	N	Nounting Face Type:
Offset Distance From Rim Centerline To Outside Wheel Mounting Face:	C	Concave
	C	Offset Distance From Rim Centerline To Outside Wheel Mounting Face:
5.125 inches	5	.125 inches

```
28
```

NSN 2530-00-700-1029

Pneumatic Tire Wheel - Page 2 of 2



Hub Characteristic: Demountable Lightening Hole Quantity: 6 Lightening Hole Hub Cap Mounting Feature: Not included **Fsc Application Data:** Non driving axle, trailer Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T307-s