NSN 2530-00-737-0734

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-737-0734 **Body Material:** Steel First End Outside Diameter: 0.875 inches Second End Outside Diameter: 0.875 inches **Mounting Provision:** Threaded mounting studs **Mounting Facility Length:** 0.760 inches **Overall Height:** 2.750 inches **Overall Width:** 7.500 inches **Bore Diameter:** 0.875 inches **Overall Diameter:** 2.650 inches **Mounting Facility Thread Class:** 2a **Mounting Facility Thread Direction:** Right-hand First End External Thread Length: 1500.000 inches **Second End External Thread Length:** 1.000 inches **Compressed Length:** 27.750 inches **Extended Length:** 41.000 inches **Mounting Provision Arrangement Style: Mounting Facility Thread Series Designator:** Unf **Mounting Facility Thread Diameter:** 0.875 inches Mounting Facility Thready Qty Per Inch (tpi): 14 **Integral Valve Operation Method:** Hydraulic **Design Characteristics:**

Single acting single cylinder

NSN 2530-00-737-0734 Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Style:
External threaded
First Piston Rod End Thread Series Designator:
Unf
First Piston Rod End Thread Diameter:
0.875 inches
First Piston Rod End Thready Qty Per Inch (tpi):
14
First Piston Rod End Thread Class:
2a
First Piston Rod End Thread Direction:
Right-hand
Piston Rod End Similarity:
Not identical
Second Piston Rod End Style:
External threaded
Second Piston Rod End Thread Series Designator:
Unf
Second Piston Rod End Thread Diameter:
0.875 inches
Second Piston Rod End Thready Qty Per Inch (tpi):
14
Second Piston Rod End Thread Class:
2a
Second Piston Rod End Thread Direction:
Right-hand
Mounting Type And Location:
Stud cylinder head end
Mounting Facility Thread Length:
1.000 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A34200