

View Online at <https://aerobasegroup.com/nsn/2530-00-738-9618>

Inside Diameter:

Between 0.463 inches and 0.483 inches

Slot Depth:

Between 0.275 inches and 0.295 inches

Groove Depth:

1.500 inches

Overall Height:

Between 1.964 inches and 2.058 inches

Overall Width:

9.240 inches

Mounting Hole Diameter:

1.500 inches

Mounting Hole Quantity:

6

Ring Style:

Rim side ring slotted

Effective Width:

7.500 inches

Mounting Bolt Circle Diameter:

Between 8.743 inches and 8.757 inches

End Application:

2320-00-498-8377

Pilot Hole Diameter:

Between 6.469 inches and 6.473 inches

Rim Style:

Flat lock

Design Type:

Integral rim

Design Form:

Disk

Hub:

Not included

Bearings:

Not included

Mounting Facility Type And Quantity:

6 stud

Ring:

Included

Mounting Type For Which Designed:

Single tire

Hole Location:

In center of rim

Disk Type:

Single

Inside Circumference:

Between 0.990 inches and 1.010 inches

Lightening Hole:

Included

Valve Hole Shape:

Round

Tire Rim Diameter:

20.000 inches

Tire:

Not included

Mounting Face Type:

Convex

Offset Distance From Rim Centerline To Outside Wheel Mounting Face:

Between 5.125 inches and 5.250 inches

Rim Style:

26

Ring Type For Which Designed:

Side

Bolt/stud Mounting Facility:

Included

Hub Characteristic:

Demountable

Lightening Hole Quantity:

6

Lightening Hole Hub Cap Mounting Feature:

Not included

Mounting Facility Bolt Circle Diameter:

8.750 inches

Fsc Application Data:

Vehicular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T307-s