## NSN 2530-00-752-0907



Brake Slack Adjuster - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/2530-00-752-0907 **Thread Direction:** Right-hand **Torque Load Rating:** 15000.000 inch-pounds **Hole Diameter:** Between 0.501 inches and 0.504 inches Major Diameter: Between 1.499 inches and 1.501 inches **Spline Quantity: Thread Size Designator:** 0.125-27 Offset Distance: 0.625 inches **Minor Diameter:** Between 1.364 inches and 1.374 inches **Screw Thread Series Designator:** Npt **Adjustment Type:** Single arm Spline Type: Straight spline **Connecting Arm Design:** Offset **Offset Direction:** Left **Connecting Arm Hole Quantity: Connecting Arm Hole Bushing:** Included Connecting Arm Center To Center Distance Between Spline Hole And Connection Hole: 5.500 inches and 4.500 inches **Connecting Arm Thickness:** Between 0.521 inches and 0.541 inches **Locking Device Type:** Spring loaded ball **Lubrication Provision:** Pipe plug Shape: Straight

Fsc Application Data: Wheel, vehicle

## NSN 2530-00-752-0907

Brake Slack Adjuster - Page 2 of 2



| _ |   |            |   |    |    |
|---|---|------------|---|----|----|
| • | n | <b>0</b> 1 | • | 12 | e: |
|   |   |            |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T129-k