NSN 2530-00-773-6075

Brake Slack Adjuster - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-773-6075

| Thread Direction: |
|---|
| Right-hand |
| Torque Load Rating: |
| 15000.000 inch-pounds |
| Hole Diameter: |
| Between 0.501 inches and 0.503 inches |
| Major Diameter: |
| Between 1.499 inches and 1.500 inches |
| Spline Quantity: |
| 10 |
| Thread Size Designator: |
| 0.125-27 |
| Offset Distance: |
| 0.625 inches |
| Minor Diameter: |
| Between 1.214 inches and 1.215 inches |
| Screw Thread Series Designator: |
| Npt |
| Adjustment Type: |
| Single arm |
| Spline Type: |
| Straight spline |
| Connecting Arm Design: |
| Offset |
| Offset Direction: |
| Left |
| Connecting Arm Hole Quantity: |
| 1 |
| Connecting Arm Hole Bushing: |
| Included |
| Connecting Arm Center To Center Distance Between Spline Hole And Connection Hole: |
| 5.500 inches |
| Connecting Arm Thickness: |
| Between 0.531 inches and 0.541 inches |
| Locking Device Type: |
| Spring loaded ball |
| Lubrication Provision: |
| Pipe plug |
| Shape: |
| Straight |
| Shelf Life: |
| N/a |
| |

NSN 2530-00-773-6075

Brake Slack Adjuster - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

T129-k

