NSN 2530-00-776-4921

Solid Rubber Tire Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-776-4921

Tread Pattern: Smooth tread Mounting Hole Diameter: Between 0.776 inches and 0.786 inches Mounting Hole Quantity: 10 Mounting Bolt Circle Diameter: Between 11.995 inches and 12.005 inches Pilot Hole Diameter:
Mounting Hole Diameter: Between 0.776 inches and 0.786 inches Mounting Hole Quantity: 10 Mounting Bolt Circle Diameter: Between 11.995 inches and 12.005 inches
Between 0.776 inches and 0.786 inches Mounting Hole Quantity: 10 Mounting Bolt Circle Diameter: Between 11.995 inches and 12.005 inches
Mounting Hole Quantity: 10 Mounting Bolt Circle Diameter: Between 11.995 inches and 12.005 inches
10 Mounting Bolt Circle Diameter: Between 11.995 inches and 12.005 inches
Mounting Bolt Circle Diameter: Between 11.995 inches and 12.005 inches
Between 11.995 inches and 12.005 inches
Pilot Hole Diameter:
Between 9.505 inches and 9.508 inches
Size Designator:
28 by 4-1/2
Tire Type:
Solid, flat tread
Design Type:
Stamped disk
Hub:
Not included
Rim:
Included
Bearings:
Not included
Tire:
Included
Hub Cap Mounting Feature:
Not included
Hub Characteristic:
Demountable
Rim Characteristic:
Integral
Integral Rim Type:
Flat base
Tire Characteristic:
Integral
Tire Arrangement Characteristic:
Single
Offset Distance From Rim Centerline To Outside Of Wheel Mounting:
0.2575 inches
Material:
Steel
Material:
Steel

NSN 2530-00-776-4921

Solid Rubber Tire Wheel - Page 2 of 2

Fsc Application Data:

Idler wheel, vehicle, full track

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T307-t

