## NSN 2530-00-776-4921

Solid Rubber Tire Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-776-4921 **Tread Pattern:** Smooth tread **Mounting Hole Diameter:** Between 0.776 inches and 0.786 inches **Mounting Hole Quantity:** 10 **Mounting Bolt Circle Diameter:** Between 11.995 inches and 12.005 inches **Pilot Hole Diameter:** Between 9.505 inches and 9.508 inches Size Designator: 28 by 4-1/2 Tire Type: Solid, flat tread **Design Type:** Stamped disk **Hub:** Not included Rim: Included Bearings: Not included Tire: Included **Hub Cap Mounting Feature:** Not included **Hub Characteristic:** Demountable **Rim Characteristic:** Integral **Integral Rim Type:** Flat base **Tire Characteristic:** Integral **Tire Arrangement Characteristic:** Offset Distance From Rim Centerline To Outside Of Wheel Mounting: 0.2575 inches Material:

Steel Material: Steel

## NSN 2530-00-776-4921

Solid Rubber Tire Wheel - Page 2 of 2



i oo Appiioalioli Ball	Fsc .	App	olication	Data
------------------------	-------	-----	-----------	------

Idler wheel, vehicle, full track

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T307-t